


NORLYS

Explore our new color palette!

- **Copper Brown (CB)** RAL8004
- **Cement Grey (CG)** RAL7033
- **Coren Steel (CS)** approx. RAL8011
- **Beige Grey (GB)** RAL7006

For more information
visit our website
norlys.com



Brightening your life with our passion for light

Inspired by the simplicity and timeless aesthetics of Scandinavian design, we draw from nature to craft lighting fixtures that exude elegance and sophistication. NORLYS products embody the core values of Scandinavian design, embracing minimalism, functionality and enduring beauty. With NORLYS, you can trust that our lighting solutions will effortlessly integrate into any space, elevating its ambiance and leaving a lasting impression.

30 + years on the market

300 + team members

24 countries

5 mln unit sold

We’re focused on our core values

At NORLYS, our values are at the core of everything we do. They shape our culture, inspire our actions, and drive our passion for delivering the best lighting solutions.
We believe that by upholding these values, we can make a positive impact on the world of lighting.



For people

We’re field experts who enjoy sharing knowledge and cherish long lasting customer relationships.

Commitment to our Clients has been our path for years, and we tread it with confidence. We support with pre-sales advice and information, and we follow up after the purchase. They can count on our openness and professionalism. They can rely on us. We put the Clients at the center of everything we do. We strive to deeply understand their varied needs, to allay fears, and surpass expectations with a wide range of diverse and unique products and services tailored to individual needs.



Responsibility

We shape the world with gentle passion, showcasing its beauty in the finest light, because it deserves nothing less.

We can’t operate any other way. We want to leave the world as we found it, with all its beauty and diversity. We responsibly use renewable resources, continuously improve energy-efficient production methods, and create top-quality luminaries with a minimal impact on the environment. Building a responsible and ethical company is a continuous, long-term effort on processes without compromises or half measures.



Passion for light

We focus on the future, emphasizing sustainability and our impact on future generations.

We strive to create extraordinary places, providing unique lighting experiences. By combining cutting-edge innovations, professionalism, enthusiasm, and the experience of our team, we obtain a powerful tool. A tool for extracting the best qualities and meanings from spaces.
Our commitment to designing unique and practical lighting solutions enriches and invigorates space.

This catalogue is not a commercial offer and we reserve the right to make changes.

Over 30 years of experience

NORLYS is the embodiment of the Scandinavian spirit. It was born in the frosty North in Norway, reflecting its simplicity, resilience, and naturalness. NORLYS is the answer to the long polar nights, the harshness of nature, and the need for safety. That is why we have been lighting spaces for 30 years. It is our passion and mission.

Today our main production plant and stock facilities are established in Poland and Sweden. We have our own aluminium foundry, a press department for the production of steel luminaires, and a hot-dip galvanising department. Apart from that, we have a machining department which includes CNC machining, a powder-coating department, and assembly departments. Our pride is our own Testing Laboratory equipped with specialised equipment of the highest class for the testing of luminaires. This lab performs measurements according to the requirements specific to ENEC and in accordance with the ISO 17025 standard.

We are an international company. Our subsidiaries located in Norway, Sweden, France, Italy and Poland are accompanied by an extensive worldwide sales network of professional distributors. This year, we are proud to announce that we have achieved the EcoVadis Bronze certification, reaffirming our commitment to sustainable development and corporate social responsibility.



Brand new production hall (1998)



Swedish warehouse (2011)




Die casting and tool shop (2011)



New warehouse and assembly (2015)

How to read the catalogue?



Families

A p.47 Alta
p.19 Arendal
p.13 Arendal Mini
p.291 Arvika
p.23 Asker
p.43 Astrid
B p.295 Basel
p.235 Bergen
p.239 Berlin
p.299 Bern
p.303 Boden
p.344 Bologna
p.53 Borg
p.61 Bornholm
p.241 Bremen
C p.331 Chelsea
p.354 Como
E p.71 Egersund
p.65 Egersund Mini
p.73 Egersund Park
F p.361 Florence
p.243 Freja
p.79 Frigga
G p.83 Geneva
p.369 Genoa
p.371 Glasgow
p.85 Grimstad
H p.97 Halden
p.87 Halmstad
p.109 Hammerfest
p.99 Hellvik
p.105 Hitra
K p.307 Karlstad
p.111 Kisa
p.115 Koster
L p.258 Larvik
p.391 Latina
p.125 Lillehammer
p.129 Lillesand
p.245 Lofoten
p.373 London
p.312 Lund
p.131 Lysfjord
M p.317 Mandal
p.411 Milano
p.393 Modena
p.136 Molde
p.141 Mora
p.143 Moss
N p.165 Namsos
p.161 Narvik
p.177 Nice
p.159 Nidaros
p.152 Nora
p.155 Nordland
O p.179 Oppland
p.260 Oslo
P p.321 Paris
p.415 Poles
p.413 Power Distributor
R p.185 Rena
p.407 Rimini
p.193 Rondane
S p.201 Sande
p.195 Sandvik
p.326 Ski
p.198 Skara
p.203 Sol
p.207 Stavanger
p.268 Stockholm
T p.223 Trysil
p.329 Vansbro
V p.215 Vasa
p.405 Venice
p.221 Varberg
p.217 Visby
p.211 Voss

Modern
Classic
Industrial
Loft

Wall

Arendal  p.15

Asker  p.25

Asker Big  p.29

Basel  p.295

Bergen  p.235

Berlin  p.238

Bern  p.299


Boden  p.303


Bologna  p.344

Borholm  p.61

Bremen  p.241

Chelsea  p.333

Chelsea  p.333

Chelsea  p.335

Chelsea Big  p.335

Como  p.354

Florence  p.361

Freja  p.243

Geneva  p.83


Genoa  p.369


Genoa Mini  p.369

Glasgow  p.371


Halden  p.97

Hitra  p.105


Karlstad  p.307


Koster  p.117


Larvik  p.258


Latina  p.391


Lillehammer  p.125

Lofoten  p.245

Lofoten  p.247

London  p.373

London  p.378

London Big  p.375

Lund  p.312

Lysfjord  p.131

Mandal  p.317

Mandal  p.317

Modena  p.393

Modena Big  p.393

Modena Big p.393

Molde p.136

Namsos p.166

Nora p.152

Nordland p.155

Oslo p.260

Paris p.323

Paris Big p.325

Rimini  p.408

Rondane  p.193

Sandvik  p.195

Sandvik  p.195

Ski  p.326

Stockholm  p.268

Stockholm  p.271

Stockholm Big  p.271

Vansbro  p.329

Vasa  p.215

Venice  p.405

Voss  p.211

Bollard

Alta  p.47

Alta  p.47

Alta  p.51

Alta  p.51

Arendal  p.19

Arendal  p.19

Arendal  p.19

Arendal Mini  p.17

Arendal Mini  p.17

Arvika  p.29`

Arvika  p.29`

Asker  p.33

Asker  p.33

Astrid  p.43

Bologna  p.347

Bologna  p.347

Borg  p.55

Borg  p.55

Borg  p.55

Borg  p.55

Chelsea  p.339

Chelsea  p.339

Chelsea Big  p.339

Chelsea Big  p.339

Como  p.356

Egersund  p.71

Egersund  p.71

Egersund Mini  p.65

Egersund Mini p.65

Egersund Park p.74

Egersund Park p.74

Florence p.364

Frigga p.79

Frigga p.79

Halmstad p.87

Halmstad p.87

Index

Halmstad  p.87

Halmstad  p.93

Halmstad  p.93

Hellvik  p.99

Hellvik  p.99

Kisa  p.111

Lillesand  p.129


Lillesand  p.129

Lofoten  p.253

Lofoten  p.255

London  p.383

London  p.383

London Big  p.383

Modena  p.397

Modena  p.397

Modena Big  p.397

Molde  p.139

Molde  p.139


Namsos  p.169


Namsos  p.169

Narvik  p.161

Oppland  p.179


Oslo  p.263


Rimini  p.407


Rimini  p.407


Skara  p.198

Stavanger  p.207

Stavanger  p.207

Stavanger  p.211

Stockholm  p.275

Stockholm  p.275

Stockholm  p.275

Stockholm  p.279

Stockholm  p.279

Stockholm  p.283

Stockholm  p.283

Stockholm Big  p.287

Trysil  p.225

Pole

Asker

p.37

Asker

p.41

Bologna

p.351

Borg

p.59

Chelsea

p.342

Como

p.359

Egersund Park

p.77

Florence

p.366

Hammerfest

p.109

Karlstad

p.310

Koster

p.121

Lofoten

p.256

London

p.387

London Big

p.387

Lund

p.315

Milano

p.411

Modena

p.401

Modena Big

p.403

Mora


p.141

Nice

p.177

Oslo

p.265

Poles

p.415

Rimini

p.411

Visby

p.217

Stockholm Big

p.287

Trysil

p.227

Electrical equipment

Power Distributor

p.413

Power Distributor

p.413

Ceiling

Bergen

p.236

Bornholm

p.59

Chelsea

p.341

Florence

p.363

Hitra

p.107

Karlstad

p.308

Latina

p.395

Lofoten

p.250

Lofoten

p.250

Lofoten

p.251

London

p.381

London Big

p.380

Modena

p.395

Modena Big

p.395

Nidaros

p.159

Nidaros

p.159

Nidaros

p.159

Nordland

p.159

Oslo

p.267

Rondane

p.197

Sandvik

p.197

Sol

p.203

Recessed & Spot

Grimstad

p.85

Grimstad

p.85

Moss

p.145

Moss

p.147

Moss

p.147

Moss


p.148

Moss

p.148


Moss

p.150

Moss

p.150

Namsos

p.173

Namsos

p.173

Namsos Mini

p.174

Rena

p.185

Rena Cover

p.189

Sande

p.201

Varberg

p.221

Arendal Mini

Luminaires that set the mood and highlight the qualities of their surroundings through beautiful light diffusion. In a modern design combining crystal with steel, the Arendal Mini will work well in a wide variety of space settings. The soft, harmonious light filtered through the satin-finished glass will introduce a pleasant atmosphere wherever it is used. The wall version of the lamp, made of aluminium, will be perfect as entrance lighting.





Arendal Mini





Colour:

- Graphite
- Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Energy under control (mainly energy-saving solutions - control, dimming, motion-dusk sensor).

Fully replaceable electrical kit.

Product Eco-friendly.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light Control
1251BL	LED	4W	330lm	3000K	> 50 000h	Dimmable
1251GR						
1252BL				4000K		
1252GR						
1250BL	E14	-	-	-	-	-
1250GR						



Arendal Mini







Colour:

Graphite
Galvanized
Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Double corrosion protection (galvanising+powder coating).


Product Eco-friendly.

Accessories:

Art. 204
Ground anchor.



Art. 203
Concreting anchor.



IP65 IK08 DIM LED Fe GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1566BL	LED	4W	330 lm	3000K	>50 000h	Dimmable
1566GA						
1566GR						
1567BL			345 lm	4000K		
1567GA						
1567GR						

IP65 IK08 DIM LED Fe GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1561BL	LED	4W	330 lm	3000K	>50 000h	Dimmable
1561GA						
1561GR						
1562BL			345 lm	4000K		
1562GA						
1562GR						



Arendal


Luminaires that set the mood and highlight the qualities of their surroundings through beautiful light diffusion. Three different heights make it easier to choose the right lamp for the garden path, driveway, terrace or house access. The effect will be even more intriguing when used together in the arragemnt. The crystal shade used in the luminaire, additionally satin-finished on the inside, provides a gentle beam of light. Arendal is modern elegance and this design never gets old.





Arendal









Colour:

Graphite
Galvanized
Black

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.



Luminaire suitable for extreme conditions.




Double corrosion protection (galvanising+powder coating).




Fully replaceable electrical kit.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IP55/65 IK08 E27 Fe GL



Art	Type of light source
1560BL	E27
1560GA	
1560GR	

IP55/65 IK08 E27 Fe GL



Art	Type of light source
1565BL	E27
1565GA	
1565GR	

IP55/65 IK08 E27 Fe GL



Art	Type of light source
1569BL	E27
1569GA	
1569GR	





Asker


Modern buildings need new solutions. The modern Asker luminaire family is ideally suited to this. Unconventional, minimalist lamps work well on a concrete or brick façade. But of course not only. The minimalist design makes it possible to match them to many variants of wall finishes, and the durable and proven materials used in the lamps guarantee many years of trouble-free use in difficult weather conditions. The lamps are also available in bollard and pole versions. The bold yet simple shapes have always been and will continue to be attractive to professional designers and individual investors alike.





Asker









Colour:

Graphite
Aluminium
Galvanized
Black
White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Multiple light variants.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).







IP65 IK08 LED E27 DALI DIM Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1510AL	LED	8,8W	312lm	3000K	50 000h	Dimmable
1510BL						
1510GR						
1510WH						
5102AL			329lm	4000K		
5102BL						
5102GR						
5102WH						
1720AL		8,4W	798lm	3000K	>70 000h	
1720BL						
1720GR						
1720WH						
5150AL		8,3W	901lm	4000K		
5150BL						
5150GR						
5150WH						
5160AL		9,9W				DALI2
5160BL						
5160GR						
5160WH						
1721AL			852lm	3000K		
1721BL						
1721GR						
1721WH						
1513AL	E27	-	-	-	-	-
1513BL						
1513GR						
1513WH						

IP44 IK08 LED E27 DIM Fe PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1700GA	LED	8,4W	360lm	3000K	50 000h	Dimmable
5100GA			367lm	4000K		
1702GA	E27	-	-	-	-	-

IP65 IK08 LED E27 DALI DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1511AL	LED	8.8W	156lm	3000K	50 000h	Dimmable
1511BL						
1511GR						
1511WH						
5103AL			164lm	4000K		
5103BL						
5103GR						
5103WH						
1726AL		5,4W	429lm	3000K	70 000h	DALI2
1726BL						
1726GR						
1726WH						
5151AL			444lm	4000K		
5151BL						
5151GR						
5151WH						
5157AL		5,5W	465lm			
5157BL						
5157GR						
5157 WH						
1727AL			426lm	3000K		
1727BL						
1727GR						
1727WH						
1514AL	E27	-	-	-	-	-
1514BL						
1514GR						
1514WH						

IP44 IK08 LED E27 DIM Fe PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1705GA	LED	8W	165lm	3000K	50 000h	Dimmable
5101GA			183lm	4000K		
1707GA	E27	-	-	-	-	-



Asker Big









Colour:

Graphite
Aluminium
Galvanized
Black
White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Multiple light variants.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).





IP65 IK08 LED E27 DIM DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1300AL	LED	8,3W	547lm	3000K	>72 000h	Dimmable
1300BL						
1300GR						
1300WH						
5080AL		19,4W	1669lm		> 70 000h	DALI2
5080BL						
5080GR						
5080WH						
5086AL		19,3W	1942lm	4000K		
5086BL						
5086GR						
5086WH						
5018AL		8,5W	550lm			Dimmable
5018BL						
5018GR						
5018WH						
1306AL		13,7W	1280lm	3000K		
1306BL						
1306GR						
1306WH						
5105AL			1313lm	4000K		
5105BL						
5105GR						
5105WH						
1303AL	E27	-	-	-	-	-
1303BL						
1303GR						
1303WH						

IP44 IK08 LED E27 DIM Fe PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1710GA	LED	7,1W	649lm	3000K	70 000h	Dimmable
1712GA	E27	-	-	-	-	-

IP65 IK08 LED E27 DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1302AL	LED	5,2W	306lm	3000K	>70 000h	Dimmable
1302BL						
1302GR						
1302WH						
5104AL			362lm	4000K		
5104BL						
5104GR						
5104WH						
5106AL		13,6W	656lm			
5106BL						
5106GR						
5106WH						
1308AL		8,4W	732lm	3000K	>72 000h	
1308BL						
1308GR						
1308WH						
5085AL		10,2W	843lm			DALI2
5085BL						
5085GR						
5085WH						
5087AL			960lm	4000K	>70 000h	
5087BL						
5087GR						
5087WH						
1305AL	E27	-	-	-	-	-
1305BL						
1305GR						
1305WH						

IP44 IK08 LED E27 DIM Fe PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1717GA	E27	-	-	-	-	-
1715GA	LED	5,3W	347lm	3000K	70 000h	Dimmable



Asker Bollard







Colour:

Graphite
Aluminium
Black

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:


Art. 1907
Concreting anchor



Art. 1908
Ground anchor




IP65 IK08 IK10 LED DALI DIM Al PMMA PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens	IK
1311AL	LED	9,5W	585lm	3000K	50 000h	-	-	IK10
1311BL								
1311GR								
1314AL		7,7W	697lm		> 109 000h	Dimmable	IESNA type II/III	IK08
1314BL								
1314GR								
1315AL		7,8W	683lm			DALI2		
1315BL								
1315GR								
1316AL		7,7W	604lm			Dimmable	IESNA type V	
1316BL								
1316GR								
1317AL		7,8W	599lm			DALI2		
1317BL								
1317GR								
1318AL		7,7W	724lm	4000K		Dimmable	IESNA type II/III	
1318BL								
1318GR								
1319AL		7,8W	706lm			DALI2		
1319BL								
1319GR								
1320AL		7,7W	617lm			Dimmable	IESNA type V	
1320BL								
1320GR								
1322AL		7,8W	616lm			DALI2		
1322BL								
1322GR								
5210AL		10W	394lm	3000K	> 55 000h	Dimmable	-	IK10
5210BL								
5210GR								
5211AL			457lm	4000K				
5211BL								
5211GR								

IP65 IK08 LED Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Motion Detector
1338AL	LED	9,7W	585lm	3000K	50 000h	PIR
1338BL						
1338GR						
1339AL			640lm	4000K		
1339BL						
1339GR						

IP65 IK08 IK10 LED DIM Al PC PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens	IK
1310AL	LED	9,5W	585lm	3000K	50 000h	On/Off	-	IK10
1310BL								
1310GR								
5120AL			636lm	4000K				
5120BL								
5120GR								
5212AL		10W	394lm	3000K	> 55 000h	Dimmable	IESNA type II/III	IK08
5212BL								
5212GR								
5213AL			458lm	4000K				
5213BL								
5213GR								
5214AL		7,7W	682lm	3000K	>109 000h			
5214BL								
5214GR								
5215AL			654lm	4000K				
5215BL								
5215GR								
5216AL			604lm	3000K			IESNA type V	
5216BL								
5216GR								
5217AL			654lm	4000K				
5217BL								
5217GR								


IP65 IK08 LED Al PC




Art	Type of light source	Watt	Luminous flux	Colour tempe-rature	L70/B50	Motion Detector
1336AL	LED	9,7W	585lm	3000K	50 000h	PIR
1336BL						
1336GR						
1337AL			636lm	4000K		
1337BL						
1337GR						



Asker Pole










Colour:

- Aluminium
- Black
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.



Fully replaceable electrical kit.




Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).




Product Eco-friendly.

Accessories:


Art. 116
Concreting anchor
For 2160 & 2360 height




Art. 117
Anchoring support
For 2160 & 2360 height.



Art. 3091
Concreting anchor




IP65 IK08 IK10 LED DIM DALI Al PMMA PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1360AL	LED	12 W	1128lm	3000K	>72 000h	Dimmable	-
1360BL							
1360GR							

*All indexes also available in 4000K and 2700K versions.


IP65 IK08 IK10 LED DIM DALI Al PMMA PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1361AL		8,4W	1081lm		> 100 000h	-	IESNA type V
1361BL							
1361GR							
1362AL		8,5W	1081lm			DALI2 / NightDim	
1362BL							
1362GR							
1366AL		8,4W	1018lm			-	IESNA type III
1366BL							
1366GR							
1368AL		8,7W	1018lm		>120 000h	DALI2 / NightDim	
1368BL							
1368GR							

*All indexes also available in 4000K and 2700K versions.


IP65 IK06 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1363AL	LED	12W	1128lm	3000K	> 72 000h	Dimmable	-
1363BL							
1363GR							

*All indexes also available in 4000K and 2700K versions.


IP65 IK06 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1364AL	LED	8,4W	1033lm	3000K	> 100 000h	-	IESNA type V
1364BL							
1364GR							
1365AL		8,5W	1085lm			DALI2 / NightDim	
1365BL							
1365GR							
1367AL		8,4W	1018lm			-	IESNA type III
1367BL							
1367GR							
1369AL		8,7W	1081lm		> 120 000h	DALI2 / NightDim	
1369BL							
1369GR							

*All indexes also available in 4000K and 2700K versions.


IP65 IK06 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
5222AL	LED	19,5W	2667lm	3000K	> 120 000h	DALI2 / NightDim	IESNA type V
5222BL							
5222GR							
5224AL			2660lm		>100 000h	Dimmable	
5224BL							
5224GR							
5226AL			2646lm			DALI2 / NightDim	IESNA type III
5226BL							
5226GR							
5228AL		19,6W	2666lm			Dimmable	
5228BL							
5228GR							

*All indexes also available in 4000K and 2700K versions.

IP65 IP55/65 IK06 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens	IP
5200AL	LED	19,9W	2620lm	3000K	> 120 000h	DALI2 / NightDim	IESNA type V	IP55/65
5200BL								
5200GR								
5202AL		19,5W	2660lm		> 100 000h	Dimmable		IP65
5202BL								
5202GR								
5204AL		19,9W	2620lm		> 120 000h	DALI2 / NightDim	IESNA type III	IP55/65
5204BL								
5204GR								
5206AL		19,6W	2666lm		> 100 000h	Dimmable		IP65
5206BL								
5206GR								

*All indexes also available in 4000K and 2700K versions.

IP65 IK10 LED DALI Al PC 60*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
4322AL	LED	19,5W	2624lm	3000K	>100 000h	DALI2 / NightDim	IESNA type II/III
4322BL							
4322GR							
4323AL			2742lm	4000K			
4323BL							
4323GR							
4362AL			2711lm	3000K			IESNA type V
4362BL							
4362GR							
4363AL			2832lm	4000K			
4363BL							
4363GR							

*Other two mounting options ø76mm and ø50mm available on request

IP65 IK10 LED DALI Al PC 60*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
4332AL	LED	39,8W	5457lm	3000K	>100 000h	DALI2 / NightDim	IESNA type II/III
4332BL							
4332GR							
4333AL			5723lm	4000K			
4333BL							
4333GR							
4372AL			5723lm	3000K			IESNA type V
4372BL							
4372GR							
4373AL			6015lm	4000K			
4373BL							
4373GR							

*Other two mounting options ø76mm and ø50mm available on request


IP65 IK10 LED DALI Al PC 6m 60*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
4342AL	LED	19,5W	2624lm	3000K	>100 000h	DALI2 / NightDim	IESNA type II/III
4342BL							
4342GR							
4343AL			2742lm	4000K			
4343BL							
4343GR							
4382AL			2711lm	3000K			IESNA type V
4382BL							
4382GR							
4383AL			2832lm	4000K			
4383BL							
4383GR							

*Other two mounting options ø76mm and ø50mm available on request

Asker Head



Asker mounted on pole 1257, further information on pages 417–418.



Colour:

- Aluminium
- Black
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.

Wide range of light direction adjustment.

Product Eco-friendly.

Accessories:

Luminaires sold separately, recommended poles ø60, further information on pages 417– 418.

IP65 | IK10 | LED | DALI | Al | PC | 6m | ⌀60*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
4352AL	LED	39,8W	5457lm	3000K	>100 000h	DALI2 / NightDim	IESNA type II/III
4352BL							
4352GR							
4353AL			5723lm	4000K			
4353BL							
4353GR							
4392AL			5723lm	3000K			IESNA type V
4392BL							
4392GR							
4393AL			6015lm	4000K			
4393BL							
4393GR							

*Other two mounting options ⌀76mm and ⌀50mm available on request



Astrid

Astrid is a fixture that catches the eye with its elegance and refined details, designed for places where aesthetics go hand in hand with functionality.

Its name, derived from an Old Norse word meaning “divine beauty”, perfectly reflects the character of this luminaire – subtle yet expressive. The ribbed structure creates an intriguing play of light and shadow as the illumination gently shines through the vertical slats after dark. Astrid was created with elegant outdoor spaces in mind – from modern residential areas and green courtyards to public spaces. Available in a full range of colours, it fits seamlessly into its surroundings and highlights their character



IP65 IK10 LED DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2208AL	LED	10,6W	256lm	3000K	> 100 000h	DALI2
2208GR						
2208BL						
2208WH						
2209AL			271lm	4000K		
2209GR						
2209BL						
2209WH						
2223AL		14,5W	369lm			
2223GR						
2223BL						
2223WH						
2222AL			356lm	3000K		
2222GR						
2222BL						
2222WH						
2212AL		10,4W	256lm			Dimmbar
2212GR						
2212BL						
2212WH						
2213AL			256lm	4000K		
2213GR						
2213BL						
2213WH						
2226AL		14,6W	377lm			
2226GR						
2226BL						
2226WH						
2225AL			362lm	3000K		
2225GR						
2225BL						
2225WH						





Astrid





220–240V IK10 IP65 LED DALI Al PMMA

Colour:

Black
Graphite
Aluminium
White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support





Alta





Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IP65 IK10 LED E27 Fe PMMA DIM




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
291BL	E27	-	-	-	-	-
291GA						
1475BL	LED E27	5,9W	100lm	2700K	25 000h	Dimmable
1475GA						
1479BL	LED	8,5W	146lm	3000K	> 50 000h	
1479GA						
5021BL			151lm	4000K		
5021GA						

IP65 IK10 LED E27 Fe PMMA DIM



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light Control
293BL	E27	-	-	-	-	-
293GA						
1477BL	LED E27	5,9W	100lm	2700K	25 000h	Dimmable
1477GA						
1476BL	LED	8,5 W	146lm	3000K	>50 000h	
1476GA						
1468BL			151lm	4000K		
1468GA						









Alta

scandinavian wood









Colour:

- Black
- Galvanized

Wood:

- Impregnated
- Painted

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.

Luminaire housing made of natural wood.


Product Eco-friendly.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IP65 IK10 E27 LED Fe DIM PMMA



Art	Type of light source
1440BL	E27
1440GA	

IP65 IK10 E27 LED Fe DIM PMMA



Art	Type of light source
1450BL	E27
1450GA	

IP65 IK10 E27 LED Fe DIM PMMA



Art	Type of light source
1443BL	E27
1443GA	

IP65 IK10 E27 LED Fe DIM PMMA



Art	Type of light source
1453BL	E27
1453GA	

Borg

The Borg luminaires family is a prime example of top quality and modern design. Borg will prove ideal for designing modern solutions to enhance urban living comfort. The Borg will be a great complement to leisurely, plant-filled squares with benches, but it will also fit in well with the landscape of an ordinary street and completely change its look. For many people, the city is a place to work and live. Therefore, designing comfortable urban landscapes requires the right eye-catching lighting. The minimalist and functional Borg will bring a modern style to any urban space.




Photo: panoramahyttene.no
CABIN GUESTS ONLY

Borg







Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:

Art. 202
Anchoring support



Art. 203
Concreting anchor



IP65 IK10 LED DIM DALI Al PMMA




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6190AL	LED	16W	1358lm	3000K	> 72 000h	Dimmable
6190GR						
6191AL			1396lm	4000K		
6191GR						
6192AL		17,6W	1358lm	3000K		DALI2 / NightDim
6192GR						
6193AL			1396lm	4000K		
6193GR						

IP65 IK10 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6180AL	LED	16W	1358lm	3000K	> 72 000h	Dimmable
6180GR						
6181AL			1396lm	4000K		
6181GR						
6183AL		15,9W				DALI2 / NightDim
6183GR						
6182AL		17,6W	1358lm	4000K		
6182GR						

IP65 IK10 LED DIM DALI AI



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6170AL	LED	16W	1358lm	3000K	> 72 000h	Dimmable
6170GR						
6171AL			1396lm	4000K		
6171GR						
6173AL		17,6W				DALI2 / NightDim
6173GR						
6172AL			1358lm	3000K		
6172GR						

IP65 IK10 LED DIM DALI AI



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6120AL	LED	16,1W	1358lm	3000K	> 72 000h	Dimmable
6120GR						
6121AL		16W	1396lm	4000K		
6121GR						
6123AL		17,2W				DALI2
6123GR						
6122AL			1358lm	3000K		
6122GR						



Borg



Borg mounted on pole 3004, details on pages 417–418.





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Product Eco-friendly.


Accessories:

Luminaires sold separately, recommended poles ø60, further information on pages 417– 418.

Art. 7660
Adapter Ø60 for install on pole Ø76



Art. 154
Arm for use on wall



IP65 IK08 LED 6m Al PC DALI 60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6150AL	LED	32W	3735lm	3000K	> 72 000h	-
6150GR						
5140AL			3928lm	4000K		
5140GR						
5141AL			3735lm	3000K		DALI2/ NightDim
5141GR						
5142AL		32,6W	3970lm	4000K		
5142GR						

IP65 IK08 LED 6m Al PC DALI 60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens Control
6151AL	LED	32W	2996lm	3000K	> 72 000h	-
6151GR						
5145AL			3069lm	4000K		
5145GR						
5146AL			2953lm	3000K		DALI2/ NightDim
5146GR						
5147AL		32,6	3194lm	4000K		
5147GR						

IP65 IK08 LED 6m DALI Al PC D4I 60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6153AL	LED	53W	6900lm	3000K	> 72 000h	DALI2 / Night-Dim
6153GR						
6154AL						D4i
6154GR						
6155AL			7200lm	4000K	> 100 000h	DALI2 / Night-Dim
6155GR						
6156AL					> 72 000h	D4i
6156GR						

Bornholm

Minimalist design, classic shape. In a word, the captivating simplicity and versatility of this lamp, which offers the possibility of many applications. The Bornholm luminaire is durable and long-lasting, and although it is dedicated to external walls, it is just as suitable for a variety of uses indoors. It can be used as a ceiling or wall light. The milky shade minimizes glare, gives evenly spread light and provides comfort to the eye. The Bornholm will be the perfect piece to bring a warm accent to this type of modern interior. It looks great on raw concrete, but will actually be a good complement to any façade or wall.





Bornholm







Colour:

Aluminium

White

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Product Eco-friendly.

IP65 IK10 LED DIM PC Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
541AL	LED	7,8W	428lm	3000K	>50 000h	Dimmable
541GR						
541WH						
5121AL			443lm	4000K		
5121GR						
5121WH						

Bornholm can be mounted as a ceiling fixture!



Egersund Mini

Energy efficiency, functionality and aesthetics. This rare combination has been achieved in this particular lams. IInnovation happens when it brings economic benefit. Undoubtedly innovative product providing efficiency, durability and low energy consumption thanks to the state-of-the-art LED technology fitted to these luminaires. Durable materials enclosed in a minimalist form and an original reflector in the shape of a metallized cone have given the lamp a completely unique appearance. It will be perfect for gardens, driveways and paths and will be a decoration for both traditional and modern homes.





Egersund Mini





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IP65 IK08 LED DIM DALI PMMA Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1290AL	LED	9,1W	864lm	3000K	> 72 000h	Dimmable
1290GR						
5117AL			917lm	4000K		
5117GR						
2302AL			864lm	3000K		DALI
2302GR						
2303AL		9,6W	934lm	4000K		
2303GR						

IP65 IK08 LED DIM DALI PMMA Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1291AL	LED	9,1W	864lm	3000K	> 72 000h	Dimmable
1291GR						
5118AL			917lm	4000K		
5118GR						
2314AL			864lm	3000K		DALI
2314GR						
2315AL			915lm	4000K		
2315GR						













Egersund





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:

Art. 1230
Concreting anchor



Art. 1231
Anchoring support



IP65 IK08 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
1280AL	LED	20,3W	1681lm	3000K	> 162 000h	Dimmable	II
1280GR							
5068AL		21,9W				DALI2 / NightDim	I
5068GR							
5014AL		20,3W	1782lm	4000K		Dimmable	II
5014GR							
5066AL		22W				DALI2 / NightDim	I
5066GR							

IP65 IK08 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
1285AL	LED	22W	1586lm	3000K	> 162 000h	Dimmable	II
1285GR							
5069AL		21,9W	1681lm			DALI2 / NightDim	I
5069GR							
5067AL			1782lm	4000K			
5067GR							
5015AL		22W				Dimmable	II
5015GR							

Egersund Park

The world takes on different and better colours in the right light. And if, in addition, the light source is stylish, durable and energy-efficient, then we have a complete success. The luminaires from the Egersund Park family are not only intended for park settings and urban greenery. The versatility of the lamps and the possibility of a variety of applications has already been appreciated by many designers. The lightweight construction, simple shape and warm light, radically changes the perception of the space.





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
6080AL	LED	9,1W	907lm	3000K	> 72 000h	Dimmable	II
6080GR							
6081AL			935lm	4000K	> 102 000h		
6081GR							
6082AL		23,9W	2258lm	3000K		DALI2 / NightDim	I
6082GR							
6083AL			2319lm	4000K			
6083GR							



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
6090AL	LED	9,1W	907lm	3000K	> 102 000h	Dimmable	II
6090GR							
6091AL			935lm	4000K			
6091GR							
6092AL		23,9W	2258lm	3000K		DALI2 / NightDim	I
6092GR							
6093AL			2319lm	4000K			
6093GR							

Egersund Park





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support





Egersund Park





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:


Art. 6130
Concreting anchor



Art. 6132
Anchoring support 490mm




Art. 6135
Electric box



for Art. 6105, 6107, 6113, 6115

IP65 IK07 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
6105AL	LED	9,1W	907lm	3000K	> 72 000h	Dimmable	II
6105GR							
6107AL			962lm	4000K			
6107GR							
6113AL		23,7W	2239lm	3000K		DALI2	I
6113GR							
6115AL		23,9W	2314lm	4000K			
6115GR							
6117AL		10W	959lm	3000K	>50 000h	Dimmable	II
6117GR							
6118AL			1064lm	4000K			
6118GR							




Frigga

Frigga delights with its simplicity and timeless style,
subtly referencing Scandinavian tradition.
The distinctive vertical pattern and elegant crystal glass shade give the fixture
a remarkably light and modern appearance. Frigga fits perfectly among garden greenery,
at the entrance to the house or on the terrace, creating an atmospheric, diffused light.
It is the perfect choice for those who appreciate classy design and seek solutions
that highlight the beauty of their surroundings without overwhelming them.




IP65 IK08 LED E27 DALI Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2147AL	E27	-	-	-	-	-
2147GR						
2147BL						
2147WH						
2153AL	LED	4,6W	322lm	3000K	> 50 000h	DALI2
2153GR						
2153BL						
2153WH						
2154AL			335lm	4000K	> 50 000h	
2154GR						
2154BL						
2154WH						

IP65 IK08 LED E27 DALI Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2148AL	E27	-	-	-	-	-
2148GR						
2148BL						
2148WH						
2150AL	LED	4,6W	322lm	3000K	> 50 000h	DALI2
2150GR						
2150BL						
2150WH						
2151AL			335lm	4000K	> 50 000h	
2151GR						
2151BL						
2151WH						

Frigga





Colour:

- Aluminium
- White
- Graphite
- Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Product Eco-friendly.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support





Geneva





Colour:

Aluminium
White
Graphite

Colour temperature:


2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Product Eco-friendly.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1874AL	E27	-	-	-	-	-
1874GR						
1874WH						
1879AL	LED	8,3W	609lm	3000K	> 72 000h	Dimmable
1879GR						
1879WH						
1880AL		8,4W	656lm	4000K		
1880GR						
1880WH						



Grimstad





220–240V IP65 IK08 IK09 LED E14 DIM AI GL

Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Product Eco-friendly.



IP65 IK09 E14 LED DIM Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1545AL	LED	8,3W	671lm	3000K	> 100 000h	Dimmable
1545GR						
5025AL		7,4W	721lm	4000K		
5025GR						
1547AL	E14	-	-	-	-	-
1547GR						

IP65 IK08 E14 LED DIM Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1544AL	LED	5,3W	214lm	3000K	70 000h	Dimmable
1544GR						
1546AL	E14	-	-	-	-	-
1546GR						





Halmstad

Thanks to Halmstad luminaires, garden spaces will acquire a unique charm. The bollard made of natural wood and steel works well with shrubs, perennials, stones and, above all, with the wooden architecture of the garden such as arbours, benches, trellises for climbing plants. Lamps in the garden are exposed to snow, sun, frost and moisture. They will serve for as long as possible heavily exposed to the test of time and weather. The elegant design with modern LED technology and the different sizes make it simply worth applying in the garden. The trees will grow larger, the plants will create a life-giving retreat and the reliable Halmstad luminaires will continue to enhance the beauty of the garden.





Halmstad







Colour:

Black
Graphite
Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Fully replaceable electrical kit.


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support




IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
296BL	E27	-	-	-	-	-
296GA						
296GR						
1483BL	LED E27	5,9W	252lm	2700K	25 000h	Dimmable
1483GA						
1483GR						
1482BL	LED	8,5W	292lm	3000K	> 50 000h	
1482GA						
1482GR						
5022BL			310lm	4000K		
5022GA						
5022GR						


IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
295BL	E27	-	-	-	-	-
295GA						
295GR						
1488BL	LED E27	5,9W	252lm	2700K	25 000h	Dimmable
1488GA						
1488GR						
1489BL	LED	8,5W	292lm	3000K	> 50 000h	
1489GA						
1489GR						
1346BL			310lm	4000K		
1346GA						
1346GR						

Bollard

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
210BL	E27	-	-	-	-	-
210GA						
210GR						
212BL	LED E27	5,9W	-	2700K	25 000h	Dimmable
212GA						
212GR						





Halmstad

scandinavian wood





220–240V IP65 IK10

LED E27 DIM Al Fe PMMA

Colour:

- Black
- Galvanized
- Graphite

Wood:

- Impregnated
- Painted

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire housing made of natural wood.

Product Eco-friendly.


Fully replaceable electrical kit.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1410BL	E27
1410GA	
1410GR	

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1400BL	E27
1400GA	
1400GR	

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1413BL	E27
1413GA	
1413GR	

Bollard

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1403BL	E27
1403GA	
1403GR	





Halden





Colour:

Aluminium

White

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

IP65 IK10 E27 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
510AL	E27	-	-	-	-	-
510GR						
510WH						
515AL	LED E27	5,9W	175lm	2700K	25000h	Dimmable
515GR						
515WH						
5096AL	LED	8,4W	662lm	3000K	> 110 000h	DALI2
5096GR						
5096WH						
517AL		8,5W	682lm			Dimmable
517GR						
517WH						
5020AL			690lm	4000K		
5020GR						
5020WH						
5097AL		8,8W	696lm			DALI2
5097GR						
5097WH						



Hellvik

The original bollard luminaire in a fashionable geometric shape will bring an aura of modernity to any private or public space. The Hellvik lamp is hard to pass by indifferently. Available in several sizes, this bollard offers a range of state-of-the-art light sources and controls to suit the most demanding users. Hellvik is the perfect choice for those who want to combine modernity with reliability and exceptional style. This lamp is a frequent choice of designers. The unusual design will work well in a wide variety of settings. Hellvik likes to play a leading role in the space. It likes to attract attention.





Hellvik









Colour:

Aluminium

Graphite

Black


Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.



Luminaire suitable for extreme conditions.




Fully replaceable electrical kit.




Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 209
Concreting anchor



Art. 2409
Anchoring support
(2 pcs needed)




IP65 LED DIM DALI Al PMMA PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
2410AL	LED	11,8W	1014lm	3000K	> 72 000h	Dimmable	II
2410BL							
2410GR							
2411AL			1072lm	4000K			
2411BL							
2411GR							
2412AL		20,2W	1747lm	3000K		DALI2	I
2412BL							
2412GR							
2413AL			1803lm	4000K			
2413BL							
2413GR							
2414AL		8W	1038lm	3000K	> 100 000h	Dimmable	II
2414BL							
2414GR							
2415AL		8,1W	1007lm	4000K			
2415BL							
2415GR							
2416AL		11,9W	1537lm	3000K		DALI2	I
2416BL							
2416GR							
2417AL			1466lm	4000K			
2417BL							
2417GR							

IP65 LED DIM DALI Al PMMA PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
2400AL	LED	6,9W	531lm	3000K	> 72 000h	Dimmable	II
2400BL							
2400GR							
2401AL			575lm	4000K			
2401BL							
2401GR							
2402AL		10,1 W	670lm	3000K		DALI2	I
2402BL							
2402GR							
2403AL			808lm	4000K			
2403BL							
2403GR							
2404AL		8W	1038lm	3000K	> 100 000h	Dimmable	II
2404BL							
2404GR							
2405AL		8,1W	1007lm	4000K			
2405BL							
2405GR							
2406AL		11,9W	1537lm	3000K		DALI2	I
2406BL							
2406GR							
2407AL			1549lm	4000K			
2407BL							
2407GR							



Hitra





Colour:

Aluminium
White
Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Product Eco-friendly.

Accessories:

Art. 151
Corner bracket tilt 15//30/45 °




IK08 IP65 LED Al GL




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
1330AL	LED	9,5W	920lm	3000K	50 000
1330GR					
1330WH					
5114AL			979lm	4000K	
5114GR					
5114WH					
1331AL		17,5W	1599lm	3000K	
1331GR					
1331WH					
5115AL			1717lm	4000K	
5115GR					
5115WH					



Hitra Ceiling





Colour:

Aluminium
White
Graphite
Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Product Eco-friendly.




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light Control
2460AL	LED	14,5W	1063lm	3000K	>100 000	DALI2
2460GR						
2460WH						
2460BL						
2462AL			1071lm	4000K		
2462GR						
2462WH						
2462BL						



Hammerfest



Hammerfest mounted on pole 3004, further information on pages 417 – 418.







Colour:

- Aluminium
- Graphite


Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.




Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Accessories:

Luminaires sold separately, recommended poles ø60, further information on pages 417 – 418.

Art. 7665
Adapter Ø60 for install on pole Ø76



Art. 154
Arm for use on wall



IP65 | LED | DALI | PMMA | Al | 6m | ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
5135AL	LED	32,3W	3320lm	4000K	> 72 000h	-
5135GR						
5136AL		32,5W	3117lm	3000K		DALI2/ NightDim
5136GR						
5137AL			3310lm	4000K		
5137GR						
6141AL		32,7W	3227lm	3000K	> 50 000h	-
6141GR						

IP65 | LED | DALI | PMMA | Al | 6m | ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
5130AL	LED	32W	3933lm	4000K	> 72 000h	-
5130GR						
5131AL		32,5W	3974lm	3000K		DALI2/ NightDim
5131GR						
5132AL			3721lm	4000K		
5132GR						
6140AL		26,4W	3321lm	3000K	> 54 000h	-
6140GR						

IP65 | LED | DALI | D4I | PMMA | Al | 6m | ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
6146AL	LED	53W	6519lm	3000K	> 100 000h	DALI2/ NightDim	IESNA type V
6146GR							
6148AL			6802lm	4000K			
6148GR							
6147AL			6545lm	3000K		D4i	
6147GR							
6149AL			7375lm	4000K			
6149GR							

Kisa

Proven, robust, practical and at the same time suitable for illuminating the driveway is the Kisa luminaire equipped with the latest LED technology. The Kisa lamp in both bollard and pole versions utilizes a huge range of LED applications, offering several control versions and light directions. Light sources must be glare-free as this is a priority for safety and convenience. In Kisa this is ensured by the milky diffuser, giving an intense but non-glare beam of light. The luminaire is also ideal for energy-saving illumination in garden settings and walkway lighting.





Kisa





CE · 220–240V · IP55 · LED · Al · DIM · DALI · PMMA

Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IP55 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
5180AL	LED	8,8W	706lm	3000K	> 70 000h	Dimmable
5180GR						
5182AL		14,1W	1185lm			DALI2/ NighDim
5182GR						
5181AL		8,8W	766lm	4000K		Dimmable
5181GR						
5183GR		14,1W	1222lm			DALI2/ NighDim
5183GR						

IP55 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
5184AL	LED	13,4W	1274lm	3000K	> 70 000h	Dimmable
5184GR						
5186AL		27W	2432lm			DALI2/ NighDim
5186GR						
5187AL			2637lm	4000K		
5187GR						
5185AL		13,4W	1357lm			Dimmable
5185GR						

Koster


The classics have always had, have and will always have their followers. The Koster lamp family is a proposal for universal lighting. Koster is a group of luminaires with a universal design characterised by a symmetrical light distribution. This design seems to tame the space, introducing calmness and predictability. The Koster luminaire can be used on the outside façade of a building, in the garden, next to a pavement. There are indeed many possibilities. It is available in a wall and two column variants – single and double.





Koster







Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 158
Corner bracket



IK10 IP45 IP54 LED DALI DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	IP	Lens
724AL	E27	-	-	-	-	-	IP54	-
724GR								
725AL	LED	9,5W	872lm	3000K	50 000h	-		
725GR								
1912AL		17,5W	1568lm					
1912GR								
5004AL			1625lm	4000K				
5004GR								
1834AL		16,9W	2090lm		>100 000h	Dimmable	IP45	IESNA type V
1834GR								
1814AL			2007lm	3000K			IP54	
1814GR								
1822AL		19,6W	2747lm		> 120 000h	DALI2/ NightDim	IP45	
1822GR								
1842AL		19,4W	2718lm	4000K				
1842GR								







Koster Pole



Koster mounted on pole 1273, further information on pages 417– 418.





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Accessories:

Luminaires sold separately, recommended poles ø50 and ø60, further information on pages 417– 418.


Art. 7660
Adapter Ø60 for mounting on pole Ø76



Art. 405
Concreting anchor



Art. 406
Anchoring support



IK10 IP65 LED DALI Al PC ∅50



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1815AL	LED	14,4W	1991lm	3000K	> 120 000h	-	IESNA type V
1815GR							
1823AL		19,4W	2747lm			DALI2/ NightDim	
1823GR			2718lm	4000K			
1843AL							
1843GR							
1835AL		14,4W	2031lm			-	
1835GR							
5070AL		17,5W	1625lm		50 000h		-
5070GR							
1915AL			1568lm	3000K			
1915GR							

IK10 IP65 LED DALI Al PC ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1817AL	LED	14,4W	1991lm	3000K	> 120 000h	-	IESNA type V
1817GR							
1825AL		19,4W	2747lm			DALI2/ NightDim	
1825GR			2718lm	4000K			
1845AL							
1845GR							
1837AL		14,4W	2031lm			-	
1837GR							
5006AL		17,5W	1625lm		50 000h		-
5006GR							
1913AL			1568lm	3000K			
1913GR							

IK10 IP65 LED DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1816AL	LED	14,4W	1991lm	3000K	> 120 000h	-	IESNA type V
1816GR							
1824AL		19,4W	2747lm			DALI2/ NightDim	
1824GR			2718lm	4000K			
1844AL							
1844GR							
1836AL		14,4W	2031lm			-	
1836GR							
5007AL		17,5W	1625lm		50 000h		-
5007GR							
1914AL			1568lm	3000K			
1914GR							

IK10 IP65 LED DIM DALI E27 PC 50




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class	Lens
1155AL	E27	-	-	-	-	-	I	-
1155GR								
1157AL	LED	35W	3136lm	3000K	> 50 000h	-		
1157GR								
1159AL			3250lm	4000K				
1159GR								
1165AL		34W	3422lm	3000K	> 120 000h	Dimmable	II	IESNA type V
1165GR								
1167AL			3624lm	4000K				
1167GR								
1173AL		37W	3654lm	3000K		DALI2/ NightDim	I	
1173GR								
1175AL			3825lm	4000K				
1175GR								

IK10 IP65 LED DIM DALI E27 PC 60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class	Lens
1177AL	E27	-	-	-	-	-	I	-
1177GR								
1179AL	LED	35W	3136lm	3000K	> 50 000h	-		
1179GR								
1181AL			3250lm	4000K				
1181GR								
1187AL		34W	3422lm	3000K	> 120 000h	Dimmable	II	IESNA type V
1187GR								
1189AL			3624lm	4000K				
1189GR								
1195AL		37W	3654lm	3000K		DALI2/ NightDim	I	
1195GR								
1197AL			3825lm	4000K				
1197GR								



Lillehammer







Colour:

- Aluminium
- Graphite
- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Multiple light variants.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



IK08 IP65 LED DIM Al GL 4° 60°




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1580AL	LED	7,3W	126lm	3000K	> 102 000h	Dimmable
1580BL						
1580GR						
1580WH						
5027AL			130lm	4000K		
5027BL						
5027GR						
5027WH						






IK08 IP65 LED DIM Al GL 60°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1581AL	LED	7,3W	216lm	3000K	> 102 000h	Dimmable
1581BL						
1581GR						
1581WH						
5028AL			231lm	4000K		
5028BL						
5028GR						
5028WH						




IK08 IP65 LED DIM Al GL 60°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1582AL	LED	4W	107lm	3000K	> 102 000h	Dimmable
1582BL						
1582GR						
1582WH						
5029AL			112lm	4000K		
5029BL						
5029GR						
5029WH						




IK08 IP65 LED DIM Al GL 4°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1583AL	LED	7,3W	34lm	3000K	> 102 000h	Dimmable
1583BL						
1583GR						
1583WH						
5030AL			38lm	4000K		
5030BL						
5030GR						
5030WH						




IK08 IP65 LED DIM 4°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1584AL	LED	4W	17lm	3000K	> 102 000h	Dimmable
1584BL						
1584GR						
1584WH						
5031AL			18lm	4000K		
5031BL						
5031GR						
5031WH						




IK08 IP65 LED DIM 4°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1585AL	LED	4W	17lm	3000K	> 102 000h	Dimmable
1585BL						
1585GR						
1585WH						
1586AL			18lm	4000K		
1586BL						
1586GR						
1586WH						



IK08 IP65 LED DIM 60°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1587AL	LED	4W	108lm	3000K	> 102 000h	Dimmable
1587BL						
1587GR						
1587WH						
1588AL			135lm	4000K		
1588BL						
1588GR						
1588WH						





Lillesand





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Product Eco-friendly.

Accessories:

Art. 205
Concreting anchor



Art. 206
Anchoring support



IK08 IP55 IP65 E27 LED DIM Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	IP
1380AL	E27	-	-	-	-	-	IP55
1380GR							
1382AL	LED E27	5,9W	495lm	2700K	25 000	Dimmable	
1382GR							
2330AL	LED	9,2W	897lm	3000K	> 72 000h		IP65
2330GR							
2331AL			956lm	4000K			
2331GR							

IK08 IP55 IP65 E27 LED DIM Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	IP
1383AL	E27	-	-	-	-	-	IP55
1383GR							
1384AL	LED E27	5,9W	495lm	2700K	25 000	Dimmable	
1384GR							
2342AL	LED	9,2W	897lm	3000K	> 72 000h		IP65
2342GR							
2343AL			956lm	4000K			
2343GR							

Lysfjord


This wall fixture can be a real discovery for designers of urban spaces and individual investors. We have used innovative configurable lens systems that allows for original lighting effects. The Lysford luminaire, although simple in shape can conjure up an extraordinary atmosphere. The various options for setting the angle of incidence of wide or focused light rays, give a very wide range of possibilities for shaping the space with light. Outstanding quality from NORLYS including aluminium, safety glass, reliable and long-lasting LED.





Lysfjord







Colour:

- Aluminium
- Graphite
- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Multiple light variants.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

IK08 IP65 LED DALI 4° 60° GL Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6401AL	LED	14,6W	946lm	3000K	> 70 000h	DALI2/ NightDim
6401BL						
6401GR						
6401WH						
6421AL				4000K		
6421BL						
6421GR						
6421WH						

IK08 IP65 LED DALI 60° 4° GL Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6402AL	LED	26,5W	946lm	3000K	> 70 000h	DALI2/ NightDim
6402BL						
6402GR						
6402WH						
6422AL				4000K		
6422BL						
6422GR						
6422WH						

IK08 IP65 LED DALI 60° 60° GL Al




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6403AL	LED	26,5W	1814lm	3000K	> 70 000h	DALI2/ NightDim
6403BL						
6403GR						
6403WH						
6423AL				4000K		
6423BL						
6423GR						
6423WH						

IK08 IP65 LED DALI 4° 4° GL Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6404AL	LED	26,5W	78lm	3000K	> 70 000h	DALI2/ NightDim
6404BL						
6404GR						
6404WH						
6424AL				4000K		
6424BL						
6424GR						
6424WH						

IK08 IP65 LED DALI 4° GL Al




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6405AL	LED	26,5W	39lm	3000K	> 70 000h	DALI2/ NightDim
6405BL						
6405GR						
6405WH						
6425AL			37lm	4000K		
6425BL						
6425GR						
6425WH						

IK08 IP65 LED DALI 4° GL Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6406AL	LED	14,6W	39lm	3000K	> 70 000h	DALI2/ NightDim
6406BL						
6406GR						
6406WH						
6426AL			37lm	4000K		
6426BL						
6426GR						
6426WH						

IK08 IP65 LED DALI 60° GL Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6407AL	LED	14,6W	998lm	3000K	> 70 000h	DALI2/ NightDim
6407BL						
6407GR						
6407WH						
6427AL			1016lm	4000K		
6427BL						
6427GR						
6427WH						

IK08 IP65 LED DALI 60° GL Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6408AL	LED	14,6W	998lm	3000K	> 70 000h	DALI2/ NightDim
6408BL						
6408GR						
6408WH						
6428AL			1016lm	4000K		
6428BL						
6428GR						
6428WH						

IK07 IP54 LED DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2026AL	LED	8W	386lm	3000K	50 000	Dimmable
2026GR						
2027AL			438lm	4000K		
2027GR						

IK07 IP54 LED Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Motion Detector
2028AL	LED	8W	386lm	3000K	50 000	PIR
2028GR						
2029AL			438lm	4000K		
2029GR						



Molde





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



Molde





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 1907
Concreting anchor



Art. 1908
Anchoring support



IK07 IP54 LED DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1901AL	LED	8W	386lm	3000K	50 000	Dimmable
1901GR						
5107AL			438lm	4000K		
5107GR						

IK07 IP54 LED Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Motion Detector
1970AL	LED	8,2W	386lm	3000K	> 55 000h	PIR
1970GR						
1972AL			438lm	4000K		
1972GR						

IK07 IP54 LED DIM Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1903AL	LED	8W	386lm	3000K	50 000	Dimmable
1903GR						
1904AL			438lm	4000K		
1904GR						

IK07 IP54 LED Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Motion Detector
1971AL	LED	8,2W	386lm	3000K	> 55 000h	PIR
1971GR						
1973AL			438lm	4000K		
1973GR						

Mora



Mora mounted on pole 1257, further information on pages 417 – 418.



Colour:

- Aluminium
- Graphite
- Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Product Eco-friendly.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Luminaires sold separately, recommended poles ø60, further information on pages 417 – 418.

IK08 IP65 LED DALI Al GL 60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6466AL	LED	33,9W	3229lm	3000K	> 110 000h	DALI2/ NigthDim
6466BL						
6466GR						
6467AL		33,5W	3437lm	4000K		
6467BL						
6467GR						

IK08 IP65 LED DALI Al GL 60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6460AL	LED	17,6W	1626lm	3000K	> 110 000h	DALI2/ NigthDim
6460BL						
6460GR						
6461AL			1735lm	4000K		
6461BL						
6461GR						

Moss


Moss spotlights combine a simple form with small dimensions. They are ideal for illuminating small architecture, individual trees or other elements of the garden layout important to the owner. Thanks to their small size, Moss can be hidden and the light will be the main feature. The undoubted strengths of this family of luminaires, thanks to the innovative use of a phase dimming system, are the ability to select the power, colour and brightness adjustment of the light source. The luminaires in the Moss family offer angle adjustment and versatility through a variety of mounting options. These include ceiling-mounted, pole-mounted, portable, driven into the ground and free-standing bollards variants.





Moss





Colour:

- Black
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Product Eco-friendly.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Wide range of light direction adjustment.

Accessories:

Art. 6437
Plate



IP65 | LED | DIM | Al | GL | 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6161BL	LED	4W	389lm	3000K	> 50 000h	Dimmable
6161GR						
6162BL			414lm	4000K		
6162GR						
6163BL		8W	686lm	3000K		
6163GR						
6164BL			749lm	4000K		
6164GR						

*All indexes also available with 15° or 24° light angle, contact your supplier.

IP65 | LED | DIM | Al | GL | 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Clamp
6732BL	LED	4W	389lm	3000K	> 50 000h	Dimmable	Ø50
6732GR							
6750BL		8W	686lm				
6750GR							
6735BL		4W	389lm				Ø60
6735GR							
6753BL		8W	686lm				
6753GR							
6738BL		4W	389lm				Ø76
6738GR							
6756BL		8W	686lm				
6756GR							

*All indexes also available in 4000K and 2700K versions, and with 15° or 24° light angle, contact your supplier.

IP65 | LED | DIM | Al | GL | 3m | 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6702BL	LED	8W	686lm	3000K	> 50 000h	Dimmable
6702GR						
6706BL		4W	389lm			
6706GR						

*All indexes also available in 4000K and 2700K versions, and with 15° or 24° light angle, contact your supplier.

Moss





Colour:

- Black
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.






Product Eco-friendly.




Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).




Wide range of light direction adjustment.

Accessories:


Art. 145
Hermetic IP68 box with 3 lines



Art. 6729
Head mount




Art. 6434 (ø50), 6435 (ø60), 6436 (ø76)
Clams.





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6165BL	LED	4W	389lm	3000K	> 50 000h	Dimmable
6165GR						
6166BL			414lm	4000K		
6166GR						
6167BL		8W	686lm	3000K		
6167GR						
6168BL			749lm	4000K		
6168GR						

*All indexes also available with 15° or 24° light angle, contact your supplier.





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6602BL	LED	4W	389lm	3000K	> 50 000h	Dimmable
6602GR						
6603BL			414lm	4000K		
6603GR						
6600BL		8W	686lm	3000K		
6600GR						
6601BL			749lm	4000K		
6601GR						

*All indexes also available with 15° or 24° light angle, contact your supplier.

*

Moss





Colour:

Black

Graphite

Stainless Steel

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Product Eco-friendly.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Wide range of light direction adjustment.

Accessories:

Art. 145
Hermetic IP68 box with 3 lines



Art. 146
8-way connection box IP68



IP65 LED DIM GL Al Fe INOX 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6346BL	LED	4W	389lm	3000K	> 50 000h	Dimmable
6346GR						
6346ST						
6352BL			414lm	4000K		
6352GR						
6352ST						
6376BL		8W	749lm			
6376GR						
6376ST						
6370BL			686lm	3000K'		
6370GR						
6370ST						

*All indexes also available with 15° or 24° light angle, contact your supplier.

IP65 LED DIM GL Al Fe INOX 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
6355BL	LED	4W	389lm	3000K	> 50 000h	Dimmable
6355GR						
6355ST						
6361BL			414lm	4000K		
6361GR						
6361ST						
6385BL		8W	749lm			
6385GR						
6385ST						
6379BL			686lm	3000K		
6379GR						
6379ST						

*All indexes also available with 15° or 24° light angle, contact your supplier.

Moss






Colour:

- Black
- Graphite
- Stainless Steel

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.






Product Eco-friendly.




Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).




Wide range of light direction adjust-ment.

Accessories:

Art. 145
Hermetic IP68 box with 3 lines




IP65 | LED | DALI | GL* | Al



* Lampenschirm Klar

Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2464AL	LED	10,3W	793lm	3000K	50 000h	DALI2
2464GR						
2464WH						
2464BL						
2473AL		15,3W	613lm			
2473GR						
2473WH						
2473BL						
2470AL			1103lm			
2470GR						
2470WH						
2470BL						
2482AL		15W	1079lm			Dimmbar
2482GR						
2482WH						
2482BL						
2488AL		6W	397lm			DALI2
2488GR						
2488WH						
2488BL						
2494AL		8W	551lm			
2494GR						
2494WH						
2494BL						

IP65 | LED | DALI | GL* | Al



* Lampenschirm Satiniert

Art	Lichtquelle	Leistung	Lichtstrom	LED-Farbe	L70/B50	Steuerung
2467AL	LED	10,3W	475lm	3000K	50 000h	DALI2
2467GR						
2467WH						
2467BL						
2491AL		6W	233lm			
2491GR						
2491WH						
2491BL						
2497AL		8W	306lm			
2497GR						
2497WH						
2497BL						
2485AL		15W	679lm			Dimmbar
2485GR						
2485WH						
2485BL						

Nora





Farbe:

- Aluminium
- Graphite
- White
- Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Product Eco-friendly.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



Nordland





Colour:

Aluminium

Graphite

White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Product Eco-friendly.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).





IP65 IK10 LED DIM DALI PC Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
718AL	LED	10W	574lm	3000K	50 000h	Dimmable
718GR						
718WH						
5016AL		9,6W	594lm	4000K		
5016GR						
5016WH						
5047AL		15,4W	933lm			
5047GR						
5047WH						
5046AL		16W	934lm	3000K		
5046GR						
5046WH						
5253AL		28,9W	2183lm		> 80 000h	DALI2
5253GR						
5253WH						
5255AL			2308lm	4000K		
5255GR						
5255WH						
7120AL	2× E27	-	-	-	-	-
7120GR						
7120WH						





Nidaros









Colour:

- Aluminium
- Graphite
- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 3084
Distance.



IP65 | LED | DIM | Al | GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2122AL	LED	8,3W	765lm	3000K	> 50 000h	Dimmable
2122BL						
2122GR						
2122WH						
2125AL		8,5W		4000K	50 000h	
2125BL						
2125GR						
2125WH						

IP65 | LED | DIM | Al | GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2121AL	LED	7,8W	765lm	3000K	>110 000h	Dimmable
2121BL						
2121GR						
2121WH						
2124AL		8,5W		4000K	50 000h	
2124BL						
2124GR						
2124WH						

IP65 | LED | DIM | Al | GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
2120AL	LED	10,7W	631lm	3000K	50 000h	Dimmable
2120BL						
2120GR						
2120WH						
2123AL				4000K		
2123BL						
2123GR						
2123WH						

Narvik

It looks robust and it really is. This bollard is a luminaire with a legendary durability that will cope perfectly with any weather conditions. The path leading to the gate, the terrace where we spend long summer evenings, the driveway – the Narvik bollard will work everywhere. The ingeniously designed diffuser emits a rotationally symmetrical stream of light, and thanks to the use of the latest technology, the luminaire provides a maximum field of illumination in relation to its size. Narvik is the ideal solution for modern architecture. It is also available in a PRO version, which, with half the power of the luminaire compared to the basic model, provides 30% more light output.





Narvik





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Vandal-resistant luminaire.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:


Art. 505
Concreting anchor



Art. 110
Ground anchor



Art. 115
Ground anchor



IK10 IP65 LED DALI DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
557AL	LED	21,8W	556lm	3000K	> 110 000h	-
557GR						
5091AL		22,5W	597lm			DALI2/ NightDim
5091GR						
5024AL		21,8W	564lm	4000K		-
5024GR						
5090AL			582lm		> 50 000h	DALI2/ NightDim
5090GR						

IK10 IP65 LED DALI DIM PMMA Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1735AL	LED	22,2W	1122lm	3000K	> 72 000h	DALI2/ NightDim
1735GR						
1850AL						-
1850GR						
559AL		13,4W	666lm			DIM
559GR						
1733AL			757lm	4000K		
1733GR						
1737AL		22,2W	1162lm			DALI2/ NightDim
1737GR						
1851AL						-
1851GR						


IK10 IP65 LED DALI DIM PMMA Al




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1736AL	LED	22,2W	1416lm	3000K	> 72 000h	DALI2/ NightDim
1736GR						
1852GR						-
1852GR						
553AL		13,6W	853lm			DIM
553GR						
1734AL		13,4W	959lm	4000K		
1734GR						
1738AL		22,2W	1475lm			DALI2/ NightDim
1738GR						
1853AL						-
1853GR						

Namsos

Lighting should give us a feeling of safety and comfort when moving around. Nasmos will be perfect for lighting stairs, steps, staircases and passageways. We recommend Namsos where you need to illuminate the most important points of your property, especially if there is a difference in level. This unusual luminaire will work perfectly as a modern lighting solution for wall surfaces and guarantees even illumination of the area under the lams. It looks equally good built into the wall as well as the bollard version.



IK09 IP65 LED DIM Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1341AL	LED	4W	123lm	3000K	> 50 000	Dimmable
1341GR						
5156AL		4,2W	162lm	4000K		
5156GR						



Namsos





CE 220–240V IK09 IP65 LED DIM AI GL

Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 157
Mounting distance





Namsos







Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 112
Concreting anchor



Art. 113
Ground anchor



IK08 IP65 LED DIM DALI AI GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1931AL	LED	8,4W	566lm	3000K	> 102 000h	Dimmable
1931GR						
5012AL		8,6W	612lm	4000K		
5012GR						
6035AL		13,8W	877lm			DALI2
6035GR						
6033AL			904lm	3000K		
6033GR						

IK08 IP65 LED DIM DALI AI GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1932AL	LED	8,6W	566lm	3000K	> 102 000h	Dimmable
1932GR						
5013AL			612lm	4000K		
5013GR						
6036AL		13,8W	877lm			DALI2
6036GR						
6034AL			904lm	3000K		
6034GR						





Namsos







Colour:

- Aluminium
- Graphite
- Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

IK08 IP65 LED DALI DIM Al GL




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1929AL	LED	13,6W	843lm	3000K	> 102 000h	Dimmable
1929GR						
1930AL		8,4W	566lm			
1930GR						
6032AL		13,8W	904lm			DALI2
6032GR						
1934AL		14W	907lm	4000K		Dimmable
1934GR						
5011AL		8,6W	612lm			
5011GR						
6031AL		13,8W	877lm			DALI2
6031GR						

IK10 IP44 LED DIM Fe GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1933GA	LED	5,2W	295lm	3000K	> 70 000	Dimmable
5116GA			689lm	4000K		

IK10 IP65 LED DIM Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1340AL	LED	4W	47lm	3000K	> 50 000h	Dimmable
1340GR						

Namsos Mini





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).





Nice



Nice mounted on pole 3004, further information on pages 417 – 418.





Colour:

- Aluminium
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Product Eco-friendly.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Accessories:

Luminaires sold separately, recommended poles ø60, further information on pages 417– 418.

Art. 154
Wall mounting arm



Art. 7665
Reduction for fittings Ø60 for mounting on a pole Ø76



IK07 IP65 LED DALI 4,5m Al GL ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
777AL	LED	38W	3029lm	3000K	> 110 000h	-
777GR						
5089GR		36,3W	2964lm		> 50 000h	DALI2/ NightDim
5089AL						
5088AL			3092lm	4000K		
5088GR						
5001AL		38W			> 110 000h	-
5001GR						



Oppland

The Oppland bollards will work fantastically between a garden path and a flower bed. They will illuminate a passage, add mystery to the plants and give depth to the garden. The Oppland luminaires family stands for energy-saving LED technology, minimalist yet elegant design, durability of materials and reliability. Choice between a modern-style aluminium body or a wooden body, in two colours, in arrangements closer to nature. Oppland bollards will not only provide exceptionally effective lighting. They will bring an elegant and modern accent to any environment that is sure to attract attention. Oppland simply illuminates beautifully.





Oppland





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 205
Concreting anchor




Art. 206
Anchoring support



IP65 IK09 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1324AL	LED	8,2W	304lm	3000K	> 171 460h	DALI2
1324GR						
1321AL					> 50 000h	Dimmable
1321GR						
5123AL		9,3W	313lm	4000K		
5123GR						







Rena





Colour:


Stainless Steel

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


CE | 220–240V | IK09 | IP68 | 3m | LED | GU10 | DIM | Al | INOX | GL | 36°




Multiple light variants.



Luminaire suitable for extreme conditions.




Fully replaceable electrical kit.




Wide range of light direction adjustment.

Accessories:


Art. 142
Ground assembly module



Art. 145
Hermetic 3-track box



Art. 146
Hermetic 3-track box



IP68 IK09 LED GU10 DIM Al INOX GL 3m 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1551ST	LED GU10	5,5W	367lm	3000K	40 000	Dimmable
1553ST		-	-	-	-	-
1762ST	LED	4W	318lm	3000K	50 000h	Dimmable
1763ST			369lm	4000K		
1766ST		8W	672lm	3000K		
1767ST			731lm	4000K		

*All indexes with LED module also available with 15° or 24° light angle, contact your supplier.
For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.

IP68 IK09 GU10 DIM Al INOX GL 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1641ST	LED GU10	5,5W	367lm	3000K	40 000	Dimmable
1643ST		-	-	-	-	-

* For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.

IP68 IK09 LED GU10 DIM Al INOX GL 3m 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1555ST	LED GU10	5,5W	237lm	3000K	40 000	Dimmable
1557ST		-	-	-	-	-
1752ST	LED	4W	178lm	3000K	50 000h	Dimmable
1753ST			180lm	4000K		
1756ST		8,8W	314lm	3000K		
1757ST		8,5W	330lm	4000K		

*All indexes with LED module also available with 15° or 24° light angle, contact your supplier.
For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.

IP68 IK09 GU10 DIM Al INOX GL 36°*



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1645ST	LED GU10	5,5W	237lm	3000K	40 000	Dimmable
1647ST		-	-	-	-	-

*For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1550ST	LED GU10	5,5W	367lm	3000K	40 000	Dimmable
1552ST		-	-	-	-	-
1760ST	LED	4W	318lm	3000K	50 000h	Dimmable
1761ST			369lm	4000K		
1764ST		8W	672lm	3000K		
1765ST			731lm	4000K		

*All indexes with LED module also available with 15° or 24° light angle, contact your supplier.
For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1640ST	LED GU10	5,5W	367lm	3000K	40 000	Dimmable
1642ST		-	-	-	-	-

*For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1554ST	LED GU10	5,5W	237lm	3000K	40 000	Dimmable
1556ST		-	-	-	-	-
1750ST	LED	4,2W	178lm	3000K	> 50 000h	Dimmable
1751ST		4W	180lm	4000K		
1754ST		8W	314lm	3000K		
1755ST			330lm	4000K		

*All indexes with LED module also available with 15° or 24° light angle, contact your supplier.
For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1644ST	LED GU 10	5,5W	237lm	3000K	40 000	Dimmable
1646ST		-	-	-	-	-

For indexes with LED GU 10 is possible to adjust the angle of the socket by 10°.



Rena Cover





Colour:

- Black
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

CE | 220–240V | IK10 | IP68 | 3m | LED | GU10 | Al | DIM | PC

Multiple light variants.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Wide range of light direction adjustment.

Accessories:


Art. 142
Power cord cover



Art. 145
Hermetic 3-track box



Art. 146
Hermetic 3-track box





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1632BL	LED GU10	-	-	-	-	-
1632GR						
1633BL		5,5W	13lm	3000K	40 000	Dimmable
1633GR						
1770BL	LED	4W	24lm	3000K	50 000h	Dimmable
1770GR						
1771BL			25lm	4000K		
1771GR						
1774BL		8,7W	48lm	3000K		
1774GR						
1775BL		8W	48lm	4000K		
1775GR						



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1630BL	LED GU10	-	-	-	-	-
1630GR						
1631BL		5,5W	13lm	3000K	40 000	Dimmable
1631GR						
1768BL	LED	4W	24lm	3000K	50 000h	Dimmable
1768GR						
1769BL			28lm	4000K		
1769GR						
1772BL		8W	48lm	3000K		
1772GR						
1773BL			56lm	4000K		
1773GR						





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1650BL	LED GU10	-	-	-	-	-
1650GR						
1651BL		5,5W	13 lm	3000K	40 000	Dimmable
1651GR						





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1652BL	LED GU10	-	-	-	-	-
1652GR						
1653BL		5,5W	13 lm	3000K	40 000	Dimmable
1653GR						



Rondane





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
538AL	E27	-	-	-	-	-
538GR						
537AL	LED	8,5W	305lm	3000K	> 110 000h	Dimmable
537GR						
539AL		17,5W	732lm		50 000h	-
539GR						
548AL		9,5W	345lm			Motion Detector
548GR						

*All indexes also available in 4000K and 2700K versions.



Sandvik







Colour:

- Aluminium
- Graphite
- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:


Art. 148
Corner bracket for art. 1730, 1731, 1732, 5152



Art. 131
Corner bracket for art 1740, 1741, 1742, 5153




IP65 IK08 LED GU10 DIM Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1730AL	LED GU10	-	-	-	-	-
1730BL						
1730GR						
1730WH						
1731AL		7,8W	420lm	2700K	40 000h	Dimmable
1731BL						
1731GR						
1731WH						
1732AL	LED	16W	1126lm	3000K	> 50 000	
1732BL						
1732GR						
1732WH						
5152AL			1350lm	4000K		
5152BL						
5152GR						
5152WH						

IP65 IK08 LED GU10 DIM Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1740AL	LED GU10	-	-	-	-	-
1740BL						
1740GR						
1740WH						
1741AL		3,9W	210lm	2700K	40 000h	Dimmable
1741BL						
1741GR						
1741WH						
1742AL	LED	8W	563lm	3000K	> 50 000h	
1742BL						
1742GR						
1742WH						
5153AL			675lm	4000K		
5153BL						
5153GR						
5153WH						

Sandvik



Colour:

Aluminium
Graphite
Black
White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
795AL	LED GU10	-	-	-	-	-
795BL						
795GR						
795WH						
796AL		3,9W	210lm	2700K	40 000h	Dimmable
796BL						
796GR						
796WH						

IP65 IK08 LED DIM PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
2937AL	LED	7,7W	730lm	4000K	>268 210h	Dimmable	IESNA Type II/III
2937BL							
2937GR							
2935AL			699lm	3000K			
2935BL							
2935GR							
2939AL			604lm				IESNA Type V
2939BL							
2939GR							
2941AL			616lm	4000K			
2941BL							
2941GR							

IP65 IK08 LED DIM PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens	Energy distributor ~230V
2945AL	LED	7,7W	730lm	4000K	>268 210h	Dimmable	IESNA Type II/III	E(Uni)
2945BL								
2945GR								
2943AL			699lm	3000K				
2943BL								
2943GR								
2947AL			604lm				IESNA Type V	
2947BL								
2947GR								
2949AL			616lm	4000K				
2949BL								
2949GR								

Skara





Colour:

Aluminium
Black
Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaires with energy distributor option.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 2934
Concreting anchor





Sande





Colour:

- Graphite
- Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

CE · 220–240V · IK08 · IP65 · LED · GU10 · DIM · Al · 5m · GL · 36° · 40°


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Wide range of light direction adjustment.

Accessories:

Art. 1233
Cap



Art. 1234
Ground anchor.



IP65 IK08 LED GU10 DIM 5m GL Al 36° 40°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Light angle
1592BL	LED GU10	5,5W	276lm	3000K	40 000	Dimmable	36°
1592GR							
1593BL	LED	8,6W	566lm		> 145 000h		40°
1593GR							

IP65 IK08 LED GU10 DIM 5m GL Al 36° 40°



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Light angle
1598BL	LED GU10	5,5W	276lm	3000K	40 000	Dimmable	36°
1598GR							
1594BL	LED	8,6W	738lm		> 145 000h		40°
1594GR							



Sol









Colour:

Aluminium
Graphite
Black
White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Product Eco-friendly.

Accessories:

Art. 3095
Distance



IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
4051AL	LED	19,1W	2101lm	3000K	> 100 000h	Dimmable
4051BL						
4051GR						
4051WH						
4052AL			2421lm	4000K		
4052BL						
4052GR						
4052WH						
4055AL			2101lm	3000K		DALI2
4055BL						
4055GR						
4055WH						
4056AL			2421lm	4000K		
4056BL						
4056GR						
4056WH						

IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
4053AL	LED	19,3W	1655lm	3000K	> 100 000h	Dimmable
4053BL						
4053GR						
4053WH						
4054AL			1905lm	4000K		
4054BL						
4054GR						
4054WH						
4057AL			1663lm	3000K		DALI2
4057BL						
4057GR						
4057WH						
4058AL			1912lm	4000K		
4058BL						
4058GR						
4058WH						

IP65 IK06 LED DIM DALI Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
4043AL	LED	19,3W	1938lm	3000K	> 100 000h	Dimmable
4043BL						
4043GR						
4043WH						
4044AL			2221lm	4000K		
4044BL						
4044GR						
4044WH						
4047AL			1924lm	3000K		DALI2
4047BL						
4047GR						
4047WH						
4048AL		19,1W	2227lm	4000K		
4048BL						
4048GR						
4048WH						

IP65 IK06 LED DIM DALI Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
4045AL	LED	19,3W	1633lm	3000K	> 100 000h	Dimmable
4045BL						
4045GR						
4045WH						
4046AL		19,1W	1890lm	4000K		
4046BL						
4046GR						
4046WH						
4049AL		19,3W	1618lm	3000K		DALI2
4049BL						
4049GR						
4049WH						
4050AL		19,1W	1866lm	4000K		
4050BL						
4050GR						
4050WH						



Stavanger





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:

Art. 1230
Concreting anchor



Art. 1231
Ground anchor



IP65 IK10 LED DIM DALI Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1240AL	LED	12,2W	428lm	3000K	> 145 000h	Dimmable
1240GR						
5008AL			493lm	4000k	50 000h	
5008GR						
5060AL						DALI2/ NightDim
5060GR						
5063AL			428lm	3000K	> 145 000h	
5063GR						

IP65 IK08 LED E27 DIM Al PMMA




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
1243AL	E27	-	-	-	-	-	I
1243GR							
2240AL	LED	13,6W	483lm	3000K	> 72 000h	Dimmable	II
2240GR							
2241AL			565lm	4000K			
2241GR							

IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1244AL	LED	12,2W	428lm	3000K	> 145 000h	Dimmable
1244GR						
5009AL		11,9W	530lm	4000k	50 000h	
5009GR						
5061AL		12,2W	493lm			DALI2/ NightDim
5061GR						
5064AL			428lm	3000K	> 145 000h	
5064GR						


IP65 IK08 LED E27 DIM Al PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
1246AL	E27	-	-	-	-	-	I
1246GR							
2244AL	LED	13,6W	483lm	3000K	> 72 000h	Dimmable	II
2244GR							
2245AL			565lm	4000K			
2245GR							


Bollard

IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1247AL	LED	8,4W	312lm	3000K	> 145 000h	Dimmable
1247GR						
5010AL			351lm	4000k	50 000h	
5010GR						
5062AL		8,5W				DALI
5062GR						
5065AL		8,4W	400lm	3000K	> 145 000h	
5065GR						

IP65 IK08 LED E27 DIM Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Class
1248AL	E27	-	-	-	-	-	I
1248GR							
2248AL	LED	8,9W	337lm	3000K	> 72 000h	Dimmable	II
2248GR							
2249AL			403lm	4000K			
2249GR							





Voss







Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Multiple light variants.

IP54 IK06 LED DIM 62° Al GL




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1951AL	LED	10,8W	557lm	3000K	> 171 460	Dimmable
1951GR						
5034AL		16,8W	610lm	4000K	50 000	
5034GR						

IP54 IK06 LED DIM 62° Al GL




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1955AL	LED	10,5W	557lm	3000K	> 102 000h	Dimmable
1955GR						
5036AL		10,5W		4000K	50 000	-
5036GR						

IP54 IK06 LED 4° 62° Al GL




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1950AL	LED	15,4W	614lm	3000K	50 000h	-
1950GR						
5032AL		16,9W	655lm	4000K	> 102 000h	
5032GR						

IP54 IK06 LED 62° 62° Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1952AL	LED	21W	1115lm	3000K	> 102 000h	-
1952GR						
5033AL			1077lm	4000K		
5033GR						

IP54 IK06 LED DIM 4° Al GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1953AL	LED	6,4W	55,7lm	3000K	> 102 000h	-
1953GR						
5128AL			55lm	4000K		Dimmable
5128GR						





Vasa







Colour:

- Aluminium
- Graphite
- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Multiple light variants.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

IP65 IK08 LED E27 DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
120AL	E27	-	-	-	-	-
120BL						
120GR						
120WH						
127AL	LED E27	8W	384lm	2700K	25 000h	Dimmable
127BL						
127GR						
127WH						
128AL	LED	8,5W	631lm	3000K	> 72 000h	
128BL						
128GR						
128WH						
5019AL		8,3W	668lm	4000K	> 70 000h	
5019BL						
5019GR						
5019WH						
5093AL		9,7W	670lm	3000K		DALI2
5093BL						
5093GR						
5093WH						
5092AL		14,1W	1039lm	4000K		
5092BL						
5092GR						
5092WH						

IP65 IK08 LED DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
450AL	LED	6W	440lm	3000K	> 102 000h	Dimmable
450BL						
450GR						
450WH						
451AL			457lm	4000K		
451BL						
451GR						
451WH						

IP65 IK08 LED DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
454AL	LED	6W	440lm	3000K	> 102 000h	Dimmable
454BL						
454GR						
454WH						
455AL			457lm	4000K		
455BL						
455GR						
455WH						

Visby

The city needs light of the right quality and in the right quantity. It needs balance. The Visby model can be an excellent choice here.
Visby is a modernist pole lamp, economical thanks to the LED modules, but also with an excellent ratio of energy consumption to lighting capacity. It is ideal for illuminating streets, built-up areas, parks and squares, where it creates practical yet beautiful lighting. This is complemented by an innovative ring bracket system at the height of the light source and a plane reflection system, which optimally reduces glare and creates a harmonious light beam.





Visby



Visby mounted on pole 3004, further information on pages 417–418.





Colour:

Aluminium

Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Product Eco-friendly.

Accessories:

Luminaires sold separately, recommended poles ø60, further information on pages 417– 418.

Art. 7660

Reduction for Ø60 luminaires for mounting on the Ø76 pole .



IP65 IK10 LED Al PMMA ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
576AL	LED	44,5W	2465lm	3000K	50 000h
576GR					
5002AL		43,6W	2624lm	4000K	
5002GR					



IP65 IK10 LED Al PMMA ∅60



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
577AL	LED	27W	1388lm	3000K	50 000h
577GR					
5003AL		26,5W	1553lm	4000K	
5003GR					





Varberg





Colour:

Aluminium

Graphite

Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Multiple light variants.

Fully replaceable electrical kit.


Product Eco-friendly.

Accessories:

Art. 6439
Special foot.



Art. 144
Electric box.



IP65 IK10 LED DALI DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
7150AL	LED	30W	3621lm	3000K	> 100 000h	DALI2/ NightDim	IESNA type IV
7150BL							
7150GR							
7151AL			3843lm	4000K			
7151BL							
7151GR							

IP65 IK08 LED DALI DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
7152AL	LED	7,7W	741lm	3000K	> 109 000h	Dimmable	IESNA type IV
7152BL							
7152GR							
7153AL		7,8W	742lm			DALI2	
7153BL							
7153GR							
7154AL		7,7W	759lm	4000K		Dimmable	
7154BL							
7154GR							
7155AL		7,8W	760lm			DALI2	
7155BL							
7155GR							

Trysil

Thoroughly futuristic, ahead of its time but elegant. Whatever your needs, Trysil is the perfect choice for those who wish to combine modernity with reliability and exceptional style. Trysil is available in bollard and pole versions. It offers a range of state-of-the-art light sources and controls, adapted to the needs of the most demanding users. Trysil family means quality, design and functionality.





Trysil









Colour:

Aluminium

Graphite

Black


Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.



Luminaire suitable for extreme conditions.




Fully replaceable electrical kit.




Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Accessories:


Art. 1907
Concreting anchor




Art. 1908
Anchoring support



Art. 1909



Art. 3081
Special foot



IP65 IK10 LED DIM Al PMMA





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1097AL	LED	7,3W	647lm	4000K	> 171 460h	Dimmable
1097BL						
1097GR						
1096AL			620lm	3000K	> 102 000h	
1096BL						
1096GR						
1108AL		9,5W	660lm		50 000h	-
1108BL						
1108GR						
1109AL			700lm	4000K		
1109BL						
1109GR						

IP65 IK10 LED DIM DALI Al PMMA





Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1101AL	LED	7,4W	694lm	4000K	> 109 000h	Dimmable	IESNA type V
1101BL							
1101GR							
1100AL			703lm	3000K			
1100BL							
1100GR							
1102AL		8W	689lm			DALI2	
1102BL							
1102GR							
1103AL			674lm	4000K			
1103BL							
1103GR							
1105AL	LED	7,4W	706lm			Dimmable	IESNA type II/III
1105BL							
1105GR							
1104AL		7,5W	738lm	3000K			
1104BL							
1104GR							
1106AL		8W	707lm			DALI2	
1106BL							
1106GR							
1107AL			693lm	4000K			
1107BL							
1107GR							

Trysil







Colour:

- Aluminium
- Black
- Graphite

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Product Eco-friendly.

Accessories:

Art. 3091



IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1048AL	LED	12,5W	1260lm	3000K	> 72 000h	Dimmable
1048BL						
1048GR						
1049AL			1300lm	4000K		
1049BL						
1049GR						
1050AL		20W	1973lm	3000K	>102 000h	DALI2/ NightDim
1050BL						
1050GR						
1051AL			2054lm	4000K		
1051BL						
1051GR						

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1055AL	LED	8,7W	1141lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1055BL							
1055GR							
1054AL		8,4W	1081lm	3000K			
1054BL							
1054GR							
1058AL		8,6W	1111lm				IESNA type II/III
1058BL							
1058GR							
1059AL		8,7W	1161lm	4000K			
1059BL							
1059GR							

IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1001AL	LED	25W	2476lm	4000K	> 102 000h	Dimmable
1001BL						
1001GR						
1000AL			2433lm	3000K		
1000BL						
1000GR						
1002AL		40W	3901lm			DALI2
1002BL						
1002GR						
1003AL			4145lm	4000K		
1003BL						
1003GR						

IP65 IK10 LED DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1007AL	LED	16,3W	2377lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1007BL							
1007GR							
1006AL			2282lm	3000K			
1006BL							
1006GR							
1010AL			2216lm				IESNA type II/III
1010BL							
1010GR							
1011AL			2293lm	4000K			
1011BL							
1011GR							

IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1060AL	LED	17W	1667lm	3000K	> 102 000h	Dimmable
1060BL						
1060GR						
1061AL			1719lm	4000K		
1061BL						
1061GR						
1062AL		20W	1973lm	3000k		DALI2/ NightDim
1062BL						
1062GR						
1063AL			2054lm	4000K		
1063BL						
1063GR						

IP65 IK10 LED DALI DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1012AL	LED	34W	3347lm	3000K	> 102 000h	Dimmable
1012BL						
1012GR						
1013AL		33W	3448lm	4000K		
1013BL						
1013GR						
1014AL		40W	3901lm	3000K		DALI2/ NightDim
1014BL						
1014GR						
1015AL			4145lm	4000K		
1015BL						
1015GR						

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1067AL	LED	12,2W	1705lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1067BL							
1067GR							
1066AL			1638lm	3000K			
1066BL							
1066GR							
1070AL			1594lm				IESNA type II/III
1070BL							
1070GR							
1071AL			1667lm	4000K			
1071BL							
1071GR							

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1019AL	LED	23,3W	3425lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1019BL							
1019GR							
1018AL			3277lm	3000K			
1018BL							
1018GR							
1022AL			3194lm				IESNA type II/III
1022BL							
1022GR							
1023AL			3308lm	4000K			
1023BL							
1023GR							

IP65 IK10 LED DIM DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1072AL	LED	17W	1667lm	3000K	> 102 000h	Dimmable
1072BL						
1072GR						
1073AL			1719lm	4000K		
1073BL						
1073GR						

IP65 IK10 LED DIM DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1024AL	LED	34W	3347lm	3000K	> 102 000h	Dimmable
1024BL						
1024GR						
1025AL			3448lm	4000K		
1025BL						
1025GR						
1026AL		40W	3901lm	3000K		DALI2/ NightDim
1026BL						
1026GR						
1027AL			4145lm	4000K		
1027BL						
1027GR						

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1079AL	LED	12,2W	1705lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1079BL							
1079GR							
1078AL			1638lm	3000K			
1078BL							
1078GR							
1082AL			1594lm				IESNA type II/III
1082BL							
1082GR							
1083AL			1667lm	4000K			
1083BL							
1083GR							

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1031AL	LED	23,3W	3425lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1031BL							
1031GR							
1030AL			3277lm	3000K			
1030BL							
1030GR							
1034AL			3194lm				IESNA type II/III
1034BL							
1034GR							
1035AL			3308lm	4000K			
1035BL							
1035GR							

IP65 IK10 LED DIM DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1084AL	LED	17W	1667lm	3000K	> 102 000h	Dimmable
1084BL						
1084GR						
1085AL			1719lm	4000K		
1085BL						
1085GR						
1086AL		20W	1973lm	3000K		DALI2/ NightDim
1086BL						
1086GR						
1087AL				4000K		
1087BL						
1087GR						

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1091AL	LED	12,2W	1705lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1091BL							
1091GR							
1090AL			1638lm	3000K			
1090BL							
1090GR							
1094AL			1594lm				IESNA type II/III
1094BL							
1094GR							
1095AL			1667lm	4000K			
1095BL							
1095GR							

IP65 IK10 LED DIM DALI Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1037AL	LED	34W	3448lm	4000K	> 102 000h	Dimmable
1037BL						
1037GR						
1036AL			3347lm	3000K		
1036BL						
1036GR						
1038AL		40W	3901lm			DALI2
1038BL						
1038GR						
1039AL			4145lm	4000K		
1039BL						
1039GR						

IP65 IK10 LED DALI Al PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Lens
1043AL	LED	23,3W	3425lm	4000K	> 100 000h	DALI2/ NightDim	IESNA type V
1043BL							
1043GR							
1042AL			3277lm	3000K			
1042BL							
1042GR							
1046AL			3194lm				IESNA type II/III
1046BL							
1046GR							
1047AL			3308lm	4000K			
1047BL							
1047GR							



Bergen






Colour:

Black

Galvanized



Luminaire suitable for extreme conditions.




Fully replaceable electrical kit.




Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 153
Corner bracket



Art. 159
Spacer



IP55 | E27 | Fe | PC



Art	Type of light source
270BL	E27
270GA	

IP55 | E27 | Fe | PC



Art	Type of light source
271BL	E27
271GA	



Bergen





220–240V
IP55
E27
PC
Fe

Colour:

Black
Galvanized

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.



IP54 IK10 E27 LED DIM Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
611BL	E27	-	-	-	-	-
611WH						
615BL	LED E27	LED max 9W	240lm	2700K	25 000h	Dimmable
615WH						
617BL	LED	8W	185lm	3000K	50 000h	
617WH						
618BL		10W	-			-
618WH						

Berlin





Colour:

Black

White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Product Eco-friendly.



Art	Type of light source
610BL	E27
610WH	




IP54 IK10 E27 LED DIM Fe PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
631BL	E27	-	-	-	-	-
631GA						
637BL	LED	8W	364lm	3000K	50 000h	Dimmable
637GA						
638BL		10W	532lm			
638GA						

Bremen





Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.



Art	Type of light source
630BL	E27
630GA	


NORLYS

Freja





Colour:

Black

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.



Art	Type of light source	Watt
1980BL	E27	2,2W



Photo: Studio Fulgseth

Lofoten





Colour:

Black

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).

IP44 IK10 E27 Fe GL



Art	Type of light source
1940BL	E27

IP44 IK10 E27 PMMA Fe



Art	Type of light source
1960BL	E27



Lofoten







Colour:

Black


Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 155
Corner bracket



IP44 E27 GL



Art	Type of light source
1939BL	E27

IP44 E27 GL



Art	Type of light source
1949BL	E27

IP44 E27 PMMA



Art	Type of light source
1963BL	E27

IP44 E27 PMMA



Art	Type of light source
1969BL	E27



Lofoten





Colour:

Black

220–240V IP44 E27 Fe GL

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).

IP44 E27 GL



Art	Type of light source
1944BL	E27

IP44 E27 GL



Art	Type of light source
1945BL	E27

Lofoten





Colour:

Black

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).



Art	Type of light source
1942BL	E27



Art	Type of light source
1962BL	E27



Lofoten





Colour:

Black

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).



Art	Type of light source
1941BL	E27



Art	Type of light source
1961BL	E27



Lofoten





Colour:

Black

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).




Art	Type of light source
1946BL	E27



Art	Type of light source
1966BL	E27

IP44 E27 GL Fe



Art	Type of light source
1948BL	E27

IP44 E27 GL Fe



Art	Type of light source
1947BL	E27

IP44 E27 PMMA Fe



Art	Type of light source
1968BL	E27

Lofoten





Colour:

Black


Luminaire suitable for extreme conditions.

Product Eco-friendly.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 405
Concreting anchor



Art. 406
Ground anchor



IP55 E27 PC Fe



Art	Type of light source
690BL	E27
690GA	



Larvik





Colour:

Black

Galvanized


Luminaire suitable for extreme conditions.

Product Eco-friendly.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 153
Mounting corner



Art. 159
Luminaire mounting distance





IP55 | E27 | PC | Fe



Art	Type of light source
240BL	E27
240GA	

Oslo



CE 220-240V IP55 E27 Fe PC

Colour:

Black

Galvanized


Luminaire suitable for extreme conditions.

Product Eco-friendly.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 153
Mounting corner



Art. 159
Luminaire mounting distance





Oslo



220–240V IP55 E27 Fe PC

Colour:

Black Galvanized

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).

IP55 E27 PC Fe



Art	Type of light source
245BL	E27
245GA	



Oslo





Colour:

- Black
- Galvanized


Luminaire suitable for extreme conditions.

Product Eco-friendly.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 405
Concreting anchor.



Art. 406
Ground anchor.



IP55 E27 PC Fe



Art	Type of light source
242BL	E27
242GA	



Oslo



220–240V IP55 E27 Fe PC

Colour:

Black

Galvanized

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).

IP55 E27 PC Fe



Art	Type of light source
240A/BL	E27
240A/GA	



IP54 IK10 E27 LED DIM PC Fe



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
220BL	E27	-	-	-	-	-
220GA						
1600BL	LED	8W	240lm	3000K	50 000h	Dimmable
1600GA						
5110BL		8W	250lm	4000K		
5110GA						

Stockholm





Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).



Art	Type of light source
226BL	E27
226GA	



Stockholm & Stockholm Big





Colour:

- Black
- Galvanized

CE · 220–240V · IP54 · Fe · E27 · PMMA


Luminaire suitable for extreme conditions.

Product Eco-friendly.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 153
Corner bracket



Art. 159
Spacer




IP54 E27 PMMA Fe



Art	Type of light source
286BL	E27
286GA	

IP54 E27 PMMA Fe



Art	Type of light source
280BL	E27
280GA	







Stockholm







Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 205
Concreting anchor.



Art. 206
Anchoring support



IP65 IK10 E27 LED DIM DALI PMMA Fe




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
288BL	E27	-	-	-	-	-
288GA						
1464BL	LED E27	5,9W	100lm	2700K	25 000h	Dimmable
1464GA						
1265BL	LED	8,5W	342lm	3000K	50 000h	
1265GA						

IP65 IK10 E27 PMMA Fe



Art	Type of light source
297BL	E27
297GA	

IP65 IK10 E27 LED DIM DALI PMMA Fe



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
289BL	E27	-	-	-	-	-
289GA						
1469BL	LED E27	5,9W	100lm	2700K	25 000h	Dimmable
1469GA						
1260BL	LED	8,5W	342lm	3000K	> 50 000h	
1260GA						
1606BL			362lm	4000K		
1606GA						


IP65 IK10 E27 PMMA Fe



Art	Type of light source
298BL	E27
298GA	

Bollard

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
299BL	E27	-	-	-	-	-
299GA						
1269BL	LED E27	5,9W	100lm	2700K	25 000h	Dimmable
1269GA						





Stockholm

scandinavian wood







Colour:

- Black
- Galvanized

Wood:

- Impregnated
- Painted

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaire housing made of natural wood.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 205
Concreting anchor.



Art. 206
Anchoring support



IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1423BL	E27
1423GA	

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1433BL	E27
1433GA	

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1420BL	E27
1420GA	

IP65 IK10 E27 LED DIM Fe PMMA



Art	Type of light source
1430BL	E27
1430GA	





Stockholm & Stockholm Big





Colour:

Black

Galvanized


CE | 220–240V | IP54 | Fe | E27 | PMMA

Luminaire suitable for extreme conditions.

Product Eco-friendly.

Double corrosion protection (galvanising+powder coating).

IP54 E27 PMMA Fe



Art	Type of light source
284BL	E27
284GA	

IP54 E27 PMMA Fe



Art	Type of light source
285BL	E27
285GA	

IP54 E27 PMMA Fe



Art	Type of light source
287BL	E27
287GA	





Stockholm Big





220-240V IP54 Fe E27 PMMA

Colour:

- Black
- Galvanized


Luminaire suitable for extreme conditions.

Product Eco-friendly.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 405
Concreting anchor.



Art. 406
Ground anchor.



IP54 E27 PMMA Fe



Art	Type of light source
281BL	E27
281GA	

IP54 E27 PMMA Fe



Art	Type of light source
283BL	E27
283GA	





Arvika







Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaires with energy distributor option.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Double corrosion protection (galvanising+powder coating).

Accessories:

Art. 208
Concreting anchor.



Art. 207
.



IP44 IK10 E27 LED PC Fe



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
891BL 891GA	LED	8,8W	543lm	3000K	> 102 000h

IP44 IK10 E27 LED PC Fe



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Energy distributor ~230V
893BL 893GA	LED	8,8W	543lm	3000K	> 102 000h	F (SHUKO)





Basel









Colour:

- Black
- Aluminium
- Galvanized
- Stainless Steel

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.



Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



Luminaire suitable for extreme conditions.




Fully replaceable electrical kit.

IP54 IK07 E27 GL Fe



Art	Type of light source
660BL	E27
660GA	
660ST	

IP54 IK07 E27 LED DIM GL Fe



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
661BL	E27	-	-	-	-	-
661GA						
661ST						
MD661BL						Motion Detector
MD661GA						
MD661ST						
668BL	LED	5,2W	483lm	3000K	> 70 000	Dimmable
668GA						
668ST						
671BL		9,5W	-		50 000h	Motion Detector
671GA						
671ST						
672BL			-	4000K		
672GA						
672ST						





Bern









Colour:

- Black
- Aluminium
- Galvanized
- Stainless Steel

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.



Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).



Luminaire suitable for extreme conditions.




Fully replaceable electrical kit.

IP54 IK07 E27 GL Fe



Art	Type of light source
650BL	E27
650GA	
650ST	

IP54 IK07 E27 LED DIM GL Fe




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
651BL	E27	-	-	-	-	-
651GA						
651ST						
655BL	LED	5,2W	477lm	3000K	> 72 000	Dimmable
655GA						
655ST						
675BL		11,2W	819lm		50 000h	Motion Detector
675GA						
675ST						
676BL			878lm	4000K		
676GA						
676ST						





Boden









Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K


*2700K on request only, contact your supplier.

Energy under control (mainly energy--saving solutions - control, dimming, motion-dusk sensor).

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

IP54 IK09 E27 Fe Al PC



Art	Type of light source
862BL	E27
862GA	

IP54 IK09 E27 LED DIM Fe Al PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
860BL	E27	-	-	-	-	-
860GA						
866BL	LED	8W	307lm	3000K	50 000h	Dimmable
866GA						
5109BL			-	4000K		
5109GA						








Karlstad





220–240V
IP55
E27
Fe
Cu
PC

Colour:

- Black
- Copper
- Galvanized
- White


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Product Eco-friendly.

Accessories:

Art. 153
Mounting corner



Art. 159
Luminaire mounting distance



IP55 | E27 | Fe | Cu | PC



Art	Type of light source
230BL	E27
230CO	
230GA	
230WH	

IP55 | E27 | Fe | PC



Art	Type of light source
230A/BL	E27
230A/GA	
230A/WH	



Karlstad



CE
220–240V
IP55
Fe
E27
PMMA

Colour:

- Black
- White
- Galvanized

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

IP55 E27 Fe PC



Art	Type of light source
2033BL	E27
2033GA	

IP55 E27 Fe PC



Art	Type of light source
2032BL	E27
2032GA	

Karlstad





220-240V IP55 Fe E27 PMMA

Colour:

Black

Galvanized


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:

Art. 405
Concreting anchor.




Art. 406
Ground anchor.





IP55 | E27 | Fe | PC



Art	Type of light source
290BL	E27
290GA	

Lund





CE 220-240V IP55 Fe E27 PC

Colour:

Black

Galvanized


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:

Art. 153
Mounting corner



Art. 159
Luminaire mounting distance





Lund



CE 220-240V IP55 E27 PC Fe

Colour:

Black

Galvanized


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:

Art. 405
Concreting anchor.



Art. 406
Ground anchor.



IP55 E27 Fe PC



Art	Type of light source
274BL	E27
274GA	

IP55 E27 Fe PC



Art	Type of light source
275BL	E27
275GA	

Mandal

An intriguing as well as functional and durable wall fixture. Scandinavian style is not only about design, but also about usability. Materials used to construct Mandal are robust and easy to maintain. Harmonious beam of light through the glass panes. It is a truly versatile luminaire that meets lighting requirements of contemporary architecture. Minimalism can be the perfect solution for any space, adding sophistication and unique character. Mandal harmonises perfectly with any type of building, but particularly in the galvanised version matches perfectly modern or industrial style.





Mandal









Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Product Eco-friendly.

Accessories:

Art. 130
Corner bracket
Art.1373, 1374



Art. 149
Corner bracket
Art.1370, 1371



IP44 IK08 GU10 DIM Fe GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1370BL	LED GU10	7,8W	500lm	2700K	40 000h	Dimmable
1370GA						
1371BL	LED GU10	-	-	-	-	-
1371GA						

IP44 IK08 GU10 DIM Fe GL



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1373BL	LED GU10	3,9W	250lm	2700K	40 000h	Dimmable
1373GA						
1374BL	LED GU10	-	-	-	-	-
1374GA						



Paris

Fashionable and elegant as a Parisian – a wall fixture that combines minimalist, industrial design and excellent functionality. Ideal for illuminating buildings and fence posts. Paris is also perfect for illuminating a house number plate. Four colour options allow for perfect match with any surroundings, both copper and galvanised versions will add exceptional character to any façade.





Paris





220–240V
IP43
Fe
LED
E27
DIM
Cu
PC

Colour:

Black

Galvanized

White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

IP43 | E27 | LED | DIM | Fe | Cu | PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
160BL	E27	-	-	-	-	-
160GA						
160WH						
1495BL	LED	5,2W	508lm	3000K	> 70 000h	Dimmable
1495GA						
1495WH						
5038BL		5,4W	476lm	4000K		
5038GA						
5038WH						

IP43 | E27 | LED | DIM | Fe | PC




Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
163BL	E27	-	-	-	-	-
163GA						
163WH						
1496BL	LED	5,2W	471lm	3000K	> 70 000h	Dimmable
1496GA						
1496WH						
5039BL		5,4W	438lm	4000K		
5039GA						
5039WH						



Paris Big









Colour:

Black
White
Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.



IP44 | IK09 | LED | DIM | Fe | PC



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control
1392BL	LED	5,2W	346lm	3000K	> 70 000h	Dimmable
1392GA						
5113BL		5,4W	432lm	4000K		
5113GA						

Ski





Colour:

Black

Galvanized

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

Luminaires with energy distributor option.adjustmen

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Light control	Energy distributor ~230V
1390BL 1390GA	LED	5,2W	371lm	3000K	> 70 000h	Dimmable	F (SCHUKO)



Vansbro



220–240V
IP55
E27
PC
Fe
Cu

Colour:

Black
Copper
Galvanized


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:

Art. 153
Mounting corner.



Art. 159
Luminaire mounting distance.



IP55 E27 PC Fe Cu



Art	Type of light source
1920BL	E27
1920CO	
1920GA	



Chelsea

Chelsea is craftsmanship, perfect workmanship and hand-blended polished copper, the result is a distinguished lighting charm. The exclusive Chelsea family offers traditional design and exceptional aesthetics. All the luminaires in the wide range are ideal for lighting entrances, terraces, walkways, driveways, gardens, fence posts. The unique style of these lamps will satisfy even the most demanding customers. An important feature of Chelsea to bear in mind that in natural weather conditions the bodies are covered with a noble patina.





Chelsea





Colour:

Copper

CE | 220–240V | IP44 | E27 | Cu | PC


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Handmade product (artisanal method).

IP44 | E27 | Cu | PC



Art	Type of light source
950CO	E27

IP44 | E27 | Cu | PC



Art	Type of light source
962CO	E27

IP44 | E27 | Cu | PC



Art	Type of light source
963CO	E27





Chelsea & Chelsea Big





Colour:

Copper

CE | 220–240V | IP44 | E27 | Cu | PC

Product Eco-friendly.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Handmade product (artisanal method).

Accessories:

Art. 152
Mounting corner.
For Art. 954, Art. 960




IP44 | E27 | Cu | PC




Art	Type of light source
955CO	E27

IP44 | E27 | Cu | PC




Art	Type of light source
964CO	E27

IP44 | E27 | Cu | PC



Art	Type of light source
954CO	E27

IP44 | E27 | Cu | PC



Art	Type of light source
960CO	E27





Chelsea & Chelsea Big





Colour:

Copper

Cu PC CE 220-240V IP44 E27

Product Eco-friendly.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Handmade product (artisanal method).

Accessories:

Art. 307
Concreting anchor.



IP44 E27 Cu PC



Art	Type of light source
941CO	E27

IP44 E27 Cu PC



Art	Type of light source
957CO	E27

IP44 E27 Cu PC



Art	Type of light source
940CO	E27

IP44 E27 Cu PC



Art	Type of light source
956CO	E27

Chelsea



CE 220–240V IP44 E27 Cu PC

Colour:

Copper

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Handmade product (artisanal method).

IP44 E27 Cu PC



Art	Type of light source
961CO	E27



IP44 E27 Cu PC



Art	Type of light source
951CO	E27

IP44 E27 Cu PC



Art	Type of light source
953CO	E27

Chelsea





Colour:
Copper

Product Eco-friendly.


Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.


Handmade product (artisanal method).

Accessories:


Art. 305
Concreting anchor.



Art. 306
Ground anchor.



Art. 108
Anchoring support.



IP54 E27 PMMA Al



Art	Type of light source
310BL	E27
310WH	

IP54 E27 PMMA Al



Art	Type of light source
311BL	E27
311WH	

IP54 E27 PMMA Al



Art	Type of light source
360BL	E27
360WH	

IP54 E27 PMMA Al



Art	Type of light source
361BL	E27
361WH	

Bologna





Colour:

Black White


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 152
Mounting corner





Bologna





CE 220-240V IP54 E27 Al PMMA

Colour:

Black White


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 307
Mounting corner



IP54 E27 PMMA Al



Art	Type of light source
312BL	E27
312WH	

IP54 E27 PMMA Al



Art	Type of light source
313BL	E27
313WH	

IP54 E27 PMMA Al



Art	Type of light source
314BL	E27
314WH	

IP54 E27 PMMA Al



Art	Type of light source
315BL	E27
315WH	





Bologna





Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:


Art. 108
Anchoring support.



Art. 305
Concreting anchor.



Art. 306
Ground anchor.



IP54 E27 PMMA Al



Art	Type of light source
362BL	E27
362WH	

IP54 E27 PMMA Al



Art	Type of light source
363BL	E27
363WH	

IP54 E27 PMMA Al



Art	Type of light source
364BL	E27
364WH	

IP54 E27 PMMA Al



Art	Type of light source
365BL	E27
365WH	





IP54 E27 PC Al



Art	Type of light source
370BL	E27
370WH	

Como



220-240V IP54 E27 Al PC

Colour:

Black White


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 152
Mounting corner.



IP54 E27 PC Al




Art	Type of light source
375BL	E27
375WH	



Como





Colour:


Black White



Product Eco-friendly.




Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.

Accessories:

Art. 307
Concreting anchor.





Como





220-240V IP54 E27 Al PC

Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:


Art. 108
Anchoring support.



Art. 305
Concreting anchor.




Art. 306
Ground anchor.



Como

IP54 E27 PC Al




Art	Type of light source
371BL	E27
371WH	

IP54 E27 PC Al



Art	Type of light source
372BL	E27
372WH	

IP54 E27 PC Al



Art	Type of light source
373BL	E27
373WH	

Florence



CE 220-240V IP54 E27 Al PC

Colour:

Black White


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 152
Mounting corner.



IP54 E27 PC Al




Art	Type of light source
800BL	E27
800WH	



Florence





Colour:


Black White




Product Eco-friendly.



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.



Art	Type of light source
800A/BL	E27
800A/WH	



IP54 E27 PC Al



Art	Type of light source
805BL	E27
805WH	

Florence



CE 220-240V IP54 E27 Al PC

Colour:

Black White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:

Art. 307
Concreting anchor.




IP54 E27 PC Al



Art	Type of light source
810BL	E27
810WH	

IP54 E27 PC Al



Art	Type of light source
820BL	E27
820WH	

IP54 E27 PC Al



Art	Type of light source
830BL	E27
830WH	

Florence





Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:


Art. 108
Anchoring support.



Art. 305
Concreting anchor.



Art. 306
Ground anchor.






Genoa & Genoa Mini





Colour:

- Black
- White





Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.





Art	Type of light source
170BL 170WH	E27





Art	Type of light source
175BL 175WH	E27



Glasgow



220-240V IP54 E27 Al PC

Colour:

- Black
- White

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

IP54 E27 PC Al




Art	Type of light source
730BL	E27
730WH	



London





Colour:


- Black
- White



Product Eco-friendly.



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.



Art	Type of light source
497BL	E27
497WH	



London Big





Colour:

- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

CE | 220–240V | IP54 | IP54/65 | Al | PC | LED | E27


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 152
Mounting corner.



IP54 E27 PC Al



Art	Type of light source
490BL	E27
490WH	

IP54 E27 PC Al



Art	Type of light source
493BL	E27
493WH	

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
4116BL	LED	9,5W	757lm	3000K	50 000h
4116WH					
4117BL			805lm	4000K	
4117WH					

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens
4118BL	LED	14,6W	1716lm	3000K	50 000h	IESNA type V
4118WH						
4119BL			1767lm	4000K		
4119WH						

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
4136BL	LED	9,5W	757lm	3000K	50 000h
4136WH					
4137BL			805lm	4000K	
4137WH					

IP54/65 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens
4138BL	LED	14,6W	1716lm	3000K	50 000h	IESNA type V
4138WH						
4139BL			1767lm	4000K		
4139WH						



IP54 | E27 | PC | Al



Art	Type of light source
480BL	E27
480WH	

IP54 | E27 | PC | Al



Art	Type of light source
481BL	E27
481WH	

London





Colour:

- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

CE | 220–240V | IP54 | IP54/65 | Al | PC | LED | E27


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 152
Mounting corner.





IP54/65 E27 LED AI



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens
4140BL	LED	17,5W	1392lm	3000K	50 000h	-
4140WH						
4141BL				4000K		
4141WH						
4142BL		14,6W	1716lm	30000K		IESNA type V
4142WH						

London & London Big





Colour:

- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.

CE | 220–240V | IP54 | IP54/65 | Al | PC | E27 | LED

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

IP54 | E27 | Al | PC



Art	Type of light source
481A/BL	E27
481A/WH	

IP54 | E27 | Al | PC



Art	Type of light source
493A/BL	E27
493A/WH	


72

London & London Big





Colour:

- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


CE | 220-240V | IP54 | LED | Al | PC | E27



Product Eco-friendly.




Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.

Accessories:

Art. 307
Concreting anchor.



IP54 E27 Al PC



Art	Type of light source
484BL	E27
484WH	

IP54 E27 Al PC



Art	Type of light source
485BL	E27
485WH	

IP54 E27 PC Al



Art	Type of light source
494BL	E27
494WH	

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
4144BL	LED	9,3W	756lm	3000K	50 000h
4144WH					





London & London Big







Colour:

- Black
- White

Colour temperature:

2700K* 3000K 4000K

*2700K on request only, contact your supplier.


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:


Art. 108
Anchoring support.



Art. 305
Concreting anchor.



Art. 306
Ground anchor.



IP54 E27 Al PC



Art	Type of light source
482BL	E27
482WH	

IP54 E27 Al PC



Art	Type of light source
483BL	E27
483WH	

IP54 E27 Al PC



Art	Type of light source
491BL	E27
491WH	

IP54 E27 Al PC



Art	Type of light source
492BL	E27
492WH	

IP54 E27 Al PC



Art	Type of light source
495BL	E27
495WH	

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
4124BL	LED	17,5W	1392lm	3000K	50 000h
4124WH					
4125BL				4000K	
4125WH					

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
4128BL	LED	19W	1514lm	3000K	50 000h
4128WH					
4129BL			1514lm	4000K	
4129WH					

IP54 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50
4132BL	LED	28,5W	2271lm	3000K	50 000h
4132WH					
4133BL			2271lm	4000K	
4133WH					

IP54/65 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens
4126BL	LED	14,6W	1716lm	3000K	> 120 000h	IESNA type V
4126WH						
4127BL			1767lm	4000K		
4127WH						

IP54/65 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens
4130BL	LED	29,2W	3422lm	3000K	> 120 000h	IESNA type V
4130WH						
4131BL			3534lm	4000K		
4131WH						

IP54/65 LED Al



Art	Type of light source	Watt	Luminous flux	Colour temperature	L70/B50	Lens
4134BL	LED	43,8W	5148lm	3000K	> 120 000h	IESNA type V
4134WH						
4135BL			5301lm	4000K		
4135WH						

Latina





Colour:

- Black
- White

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.



Art	Type of light source
105BL	E27
105WH	




Modena & Modena Big





Colour:

- Black
- White






Product Eco-friendly.




Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.

Accessories:

Art. 152
Corner bracket



IP54 E27 Al PC



Art	Type of light source
350BL	E27
350WH	

IP54 E27 Al PC



Art	Type of light source
351BL	E27
351WH	

IP54 E27 Al PC



Art	Type of light source
380BL	E27
380WH	

IP54 E27 Al PC



Art	Type of light source
381BL	E27
381WH	

Modena & Modena Big





Colour:

- Black
- White

CE · 220–240V · IP54 · E27 · Al · PC

Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

IP54 · E27 · Al · PC



Art	Type of light source
351A/BL	E27
351A/WH	

IP54 · E27 · Al · PC



Art	Type of light source
381A/BL	E27
381A/WH	



Modena & Modena Big





Colour:

- Black
- White

CE · 220–240V · IP54 · E27 · Al · PC


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 307
Concreting anchor.



IP54 E27 Al PC



Art	Type of light source
304BL	E27
304WH	

IP54 E27 Al PC



Art	Type of light source
300BL	E27
300WH	

IP54 E27 Al PC



Art	Type of light source
384BL	E27
384WH	





Modena





Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:


Art. 305
Concreting anchor.



Art. 306
Ground anchor.



Art. 108
Anchoring support.



IP54 E27 Al PC



Art	Type of light source
302 BL	E27
302WH	

IP54 E27 Al PC



Art	Type of light source
303BL	E27
303WH	

Modena Big





Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:


Art. 305
Concreting anchor.



Art. 306
Ground anchor.



Art. 108
Anchoring support.



IP54 E27 Al PC



Art	Type of light source
301BL	E27
301WH	

IP54 E27 Al PC



Art	Type of light source
382BL	E27
382WH	

IP54 E27 Al PC



Art	Type of light source
397BL	E27
397WH	

Venice





Colour:


- Black
- White



Product Eco-friendly.



Luminaire suitable for extreme conditions.



Fully replaceable electrical kit.





Art	Type of light source
261BL	E27
261WH	



Rimini





Colour:

- Black
- White

CE | 220-240V | IP54 | E27 | Al | PC


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 307
Concreting anchor.



IP54 E27 Al PC



Art	Type of light source
250BL	E27
250WH	

IP54 E27 Al PC



Art	Type of light source
404BL	E27
404WH	

IP54 E27 Al PC



Art	Type of light source
259BL	E27
259WH	

IP54 E27 Al PC



Art	Type of light source
2591BL	E27
2591WH	

Rimini





220–240V IP54 E27 Al PC

Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fully replaceable electrical kit.

Accessories:

Art. 150
Corner bracket





Rimini & Milano







Colour:

- Black
- White


Product Eco-friendly.

Luminaire suitable for extreme conditions.


Fully replaceable electrical kit.

Accessories:

Art. 405
Concreting anchor.



Art. 406
Ground anchor.



IP54 E27 Al PC



Art	Type of light source
401BL	E27
401WH	

IP54 E27 Al PC



Art	Type of light source
402BL	E27
402WH	

IP54 E27 Al PC



Art	Type of light source
403BL	E27
403WH	

Power Distributor





Colour:

- Black
- White
- Graphite
- Aluminium


Product Eco-friendly.

Luminaire suitable for extreme conditions.

Fixture with energy distributor option.

Accessories:

Art. 2934
Concreting anchor



IP54 Al



Art	Socket
2900AL	E (Uni)
2900BL	
2900GR	
2900WH	
2902AL	F(SCHUKO)
2902BL	
2902GR	
2902WH	

IP54 Al




Art	Socket
2901AL	E (Uni)
2901BL	
2901GR	
2901WH	
2903AL	F(SCHUKO)
2903BL	
2903GR	
2903WH	

Poles

Poles




Art. 1277



Colour:

AL BL GR


Art. 1275



Colour:

AL BL GR


Art. 1273



Colour:

AL BL GR


Art. 3009



Colour:

Galvanized

Art. 3011




Colour:


BL WH

Accessories:

Art. 405
Concreting anchor.




Art. 406
Ground anchor.



Poles


Poles





Art. 3004 Art. 3005


Art. 3005 includes concreting anchor 7663.



Colour:

AL BL GR


Art. 2000



Colour:

AL BL GR


Art. 1255



Colour:

AL BL GR


Art. 1257



Colour:

AL BL GR

Art. 30101




Colour:

BL WH

Art. 3013


Art. 3013 includes terminal.



Colour:

BL WH

Art. 3010




Colour:

BL WH

Accessories:


Art. 7661

Electric box




Art. 7662

Pole connector.




Art. 7663

Concreting anchor




Art. 144

Pole conector




Art. 305

Concreting anchor




Art. 306

Ground anchor



Special Icons




Natural Scandinavian wood.

We use only high-quality, natural Scandinavian wood, which adds warmth and elegance to the lamps. The natural Scandinavian wood used in the fittings refers to the Nordic style, its naturalness, lightness and subtlety.



Luminaires with energy distributor option adjustment.

Some of our lamps offer the possibility of energy distribution, allowing additional appliances or other lighting elements to be connected.




Fully replaceable electrical kit.

If required, our lamps allow for easy replacement of electrical components, ensuring a longer product life.



Handmade product (artisanal method).

Each lamp is meticulously handcrafted using traditional craftsmanship methods to guarantee its unique character. The power of craftsmanship.



Multiple light variants adjustment.

We offer a variety of lighting modes, from soft light to strong illumination, adapting to different lighting needs.



Vandal-resistant luminaire.

Our lamps are robustly manufactured and vandal-resistant, making them an ideal choice for public areas.




Product Eco-friendly.

We care about the environment. Our products are environmentally friendly and manufactured with minimal environmental impact in mind.




Luminaire suitable for extreme conditions.

The lampconstruction is resistant to extreme weather conditions, from frost to heat, guaranteeing its durability.



Wide range of light direction.

Our lamps are equipped with an adjustable head, allowing the direction of light to be set precisely according to individual needs.



Double corrosion protection (galvanising+powder coating).

Each lamp is protected against corrosion twice, first by galvanising and then by powder coating. This guarantees its longevity and resistance to weathering.



Energy under control (mainly energy-saving solutions - control, dimming, motion-dusk sensor).

Our garden lights offer advanced energy control features that allow significant savings. Features such as light dimming, motion sensor and twilight sensor ensure that the light shines only when it is needed

Icons

Product Characteristics



Luminaire with socket for replaceable light source (GU10, E27, E14)



Luminaire with socket for interchangeable light sources.



LED luminaire

Luminaire equipped with LED module



Voltage 220–240V

Control



Motion sensor

Luminaire equipped with a motion sensor.



DIM dimmable version

Phase dimmable luminaire



DALI light control



Light control in the D4i system

Security



CE Certificate

CE - Manufacturers declaration that a labelled product complies with the requirements of the EU'p.so-called ‚New Approach' directive

---

Protection class (I, II, III)




Protection class I/ Luminaire with protective conductors.



Protection class II/protection by double or reinforced insulation.




Protection class III/low voltage protection.



IP

IP rating, determines whether the electrical equipment is suitable for various environmental conditions

---



IK


The IK shock resistance level is a measure of the resistance of electrical equipment enclosures to mechanical stress, particularly impact stress

Connection / application




Specified inrun strength (for recessed luminaires)

Overrun luminaire (for vehicles with pneumatic tyres)



Length of cable with plug or lngth of cable with open end.




Diameter of luminaire mounting on pole.

Light emission



Light (up, down)

Determination of the direction of the light beam emission.



Light (narrow down - wide up, narrow up, etc.)

Determination of the direction and angle of the light beam emission.



Swivel and tilt range

Adjustable light direction.



Light angle

Determination of the angle of the light beam emission.

Main and visual materials used



Steel



Stainless steel



Aluminium



Copper



Wood

Type of lens



Toughened / safe glass

Luminaire with safe glass diffuser.



PMMA (acrylic glass)

The luminaire uses PMMA (acrylic glass) diffuser.



PC (polycarbonate)

The luminaire uses PC (polycarbonate) diffuser.

NORLYS

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway

+47 24 12 40 10
www.norlys.com
firmapost@norlys.no